

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27781
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-5136
7. Lease Name or Unit Agreement Name Devon State
8. Well No. 2
9. Pool name or Wildcat E. Millman-Q-GR-SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	RECEIVED
2. Name of Operator SDX RESOURCES, INC.	JUN 21 '94
3. Address of Operator P. O. BOX 5061, MIDLAND, TX 79704	C. C. D.
4. Well Location Unit Letter <u>L</u> : <u>330</u> Feet From The <u>West</u> Line and <u>2310</u> Feet From The <u>South</u> Line Section <u>23</u> Township <u>19-S</u> Range <u>28-E</u> NMPM <u>EDDY</u> County <u></u>	ARTESIA, OFFICE
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3385 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

- 3-03-94 Spud well. Drill 375' of 12 1/4" hole. Run 8 5/8" 24# J-55 csg to 371'. Cement with 350 sx Class "C" cement. Circulate 35 sx. WOC 18 hours. Test csg and BOP: 1,000# for 30 minutes and held okay. Drilled 7 7/8" hole to 2755' TD.
- 3-10-94 Ran LDT-CNL-GR & DLL-GR open hole logs. Ran 20 jts 5 1/2", J-55, 15.5# csg (626') and 50 jts of 5 1/2", J-55, 14# csg (2116') set at 2754'. Cement with 325 sx 50/50 POZ and 500 sx "Lite". Circulated 94 sx cement.
- 5-06-94 Tag PBTD at 2705'. Perforate 1 spf 26 holes: 2206, 11, 20, 21, 22, 32, 36, 70, 76, 2310, 18, 34, 40, 52, 60, 66, 77, 84, 94, 98, 2402, 32, 38, 58, 64. Acidize with 3000 gal 15% Ferchek. Frac with 40,000 gal X/L Borate gel and 110,000# of 12/20 sand. Set RBP at 2156' and perf 1 spf 26 holes: 1950, 52, 56, 58, 90, 91, 2000, 01, 12, 43, 44, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 2100, 02, 07. Acidize with 3000 gal 15% Ferchek. Frack with 40,000 gal X/L Borate gel and 110,000# of 12/20 sand. Circ 130' sand to 2156' and release RBP. Circ 110' sand to 2705'. Land tbg off at 2566', run rods and pump. Begin pumping back load.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Barbara E. Wickham TITLE Prod. Analyst DATE 05-20-94

TYPE OR PRINT NAME Barbara E. Wickham TELEPHONE NO. 685-1761

(This space for State Use)

APPROVED BY SUPERVISOR, DISTRICT II TITLE  DATE OCT 31 1994

CONDITIONS OF APPROVAL, IF ANY: