

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

MAR 18 1994

WELL API NO. 30-015-27868
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Carl TP Com
8. Well No. 4
9. Pool name or Wildcat South Dagger Draw Upper Penn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3657' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South 4th St., Artesia, NM 88210 (505) 748-1471	4. Well Location Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line Section 22 Township 20S Range 24E NMPM Eddy County
--	--	---	--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole with Auger Air 12:00 Noon 3-7-94. Set 80' of 20" conductor and redi-mix to surface. Resumed drilling 14-3/4" hole 7:30 PM 3-12-94. Ran 24 joints 36# 9-5/8" J-55 (1079') casing set 1075'. Guide shoe set 1075', insert float set 1030'. Cemented w/100 sx "H" with 12% Thixad, 10#/sx Gilsonite + 1/2#/sx Celloseal + 1% CaCl2 (yield 1.54, wt 14.6). and 800 sx PSL "C" with 6% gel, 10#/sx Gilsonite + 1/2#/sx Celloseal + 3% CaCl2 (yield 1.99, wt 12.5). Tailed in with 200 sx Class "C" Neat with 2% CaCl2 (yield 1.33, wt 14.8). PD 5:45 PM 3-14-94. Bumped plug to 900 psi, float held OK. Circulated 198 sacks to pit. WOC. Drilled out 11:45 AM 3-15-94. WOC 18 hrs. NU and tested to 1000 psi for 15 minutes. Cut off and welded on flow nipple. Reduced hole to 8-3/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 3-17-94
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: