

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No 1004-0135
Expires March 31, 1991

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Devon Energy Corporation (Nevada)

3. Address and Telephone No.
20 N. Broadway, Suite 1500, OKC, OK 73102-8260 405/235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit E, Sec. 35-18S-31E, 1650' FNL & 990' FWL

5. Lease Designation and Serial No
NM10190

6. If Indian, Allottee or Tribe Name
N/A

7. If Unit or CA, Agreement Designation
14-08-001-11572

8. Well Name and No
East Shugart Unit # 47

9. API Well No.
30-015-27871

10. Field and Pool, or Exploratory Area
Shugart (Y-SR-Q-G)

11. County or Parish, State
Eddy, NM

CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other perf Queen, acidize
and frac

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-04-94 thru 10-19-94 Wedge WL ran CBL from 3969' to surf. Bond looks good across zones of interest. Perf'd w/1 SPF: LQ2 at 3797-3800' w/4 holes, LQ3 at 3850-3852' w/3 holes, LQ4 at 3862-3870' w/9 holes; total 16 holes. Ran Baker full bore packer on 2 7/8" tbg to 3870'. Spotted acid across perfs. Pulled packer to 3700' and set. Newsco acidized LQ2,3&4 perfs 3797-3870' w/1500 gals 15% NeFe acid + 32 BS. Balled out. AIR 4.8 BPM w/1800 psi, Max 4.8 BPM w/4000 psi. ISIP 1180 psi, 15 mins 980 psi. Swab tested. POH w/tbg and packer. Newsco Frac'd LQ2,3&4 perfs at 3797-3870' down csg w/1000 gals prepad containing 2 drums of scale inhibitor + 19,000 gals X-link gelled 2% KCl + 63,000# 20/40 Ottawa sd + 12,000# 20/40 RC sd. Well screened out w/3000# 20/40 RC sd in formation. AIR 25 BPM w/1780 psi, Max 25 BPM w/4400 psi. Well flwd a total of 155 BLW and died. Ran tbg open ended. Tagged sand at 3889'. Circ'd sand to 3969'. POH w/2 7/8" tbg. Atlas WL ran Prism Log from 3955-3550'. Ran MA open ended 2 7/8" 6.5# J-55 8rd (set at 3878'), SN 2 7/8" (set at 3843.15'), 114 jts 2 7/8" 6.5# J-55 8rd tbg. Ran 2 1/2" x 2" x 16' BHD pump and rods. Pump testing. RU L&R WS pulling unit. Long stroked pump. Pulled rods and pump. Tagged sand at 3980'. Circ'd sand to 3969'. Pulled tbg. Put bull plug on MA. Ran MA, perf'd sub, SN and 114 jts 2 7/8" tbg. Ran 2 1/2" x 1 3/4" x 16' BHD pump and rods. Pump testing.

14. I hereby certify that the foregoing is true and correct

Signed Candace R. Graham

Title Engineering Tech.

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

NOV 15 1994

CARLSBAD, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.