Form 3160-5 (June 1990) RECEIVED

UPSTED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Drawer DD Artesia, NM 88210

CIST

FORM APPROVED

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE 1. Type of Well		5. Lease Designation and Serial No. NM10191 6. If Indian, Allottee or Tribe Name N/A
		⊠ Oil ☐ Gas ☐ Other
2. Name of Operator DEVON ENERGY CORPORATION (NEVADA) 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-3611 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) Sec. 35-T18S-R31E, Unit B, 990' FNL & 1500' FEL		8. Well Name and No. East Shugart Unit #49
		9. API Well No.
		30-015-27873
		10. Field and Pool, or Exploratory Area
		Shugart (Y-SR-Q-G) 11. County or Parish, State
	C 0.	Eddy Cnty, NM
	O. C. O. F.	ACE.
CHECK ADDDODDIATE DOV	((s) TO INDICATE NATURE OF NOTICE, REPO	ORT OR OTHER DATA
		JKI, OKOTILK DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Spud and running casing	Dispose Water (Note: Report results of multiple completion on Well
	ll pertinent details, and give pertinent dates, including estimated date of starting any pr	Completion or Recompletion Report and Log form.)
float collar at 894'. Cemented w/300 200 sx Class C w/2% CaCl ₂ (mixed a 2230 hrs 09-23-94.	to 950'. Ran 22 jts 8 5/8" 24# J-55 8rd EUE cs sxs lite w/2% CaCl ₂ + 1/4# Celloflake/sx (mixed to 14.8 ppg= 1.32 cf/sx yield). 58 sx cement circ's	d at 12.9 ppg= 1.84 cf/sx yield) + d to surface. Job complete at
8rd csg (4078.74'), shoe set at 4043' Cemented w/400 sx Lite w/5# salt/sx	tlas ran ZDL/CN/GR/C and DLL/MLL/GR/C log f, float collar at 3983.85, 20 centralizers. Preced t + 1/4# Celloflake/sx (mixed at 12.7 ppg= 1.97 controller reformer + 1/4# Celloflake/sx (mixed at 14.8 ppg 5 hrs 09-29-94.	ded cement by 500 gals mud flush. cf/sx yield) and 500 sx Class C
Released rig at 0445 hrs 09-29-94.	Waiting on completion.	
14. I hereby certify that the foregoing is true and correct	CANDI GRAHAM	
Signed Candace K. Draho	Title ENGINEERING TECHNICIAN	Date 10/5/94
(This space for Federal or State office use)		
	Title	Date of 1004
Approved by	Title	- '' 1994
annument of alternative and.		N