



11800 COUNTY ROAD 125 WEST

P.O. BOX 80130

MIDLAND, TEXAS 79

Post-it™ brand fax transmittal memo 7671

# of pages &gt;

To <i>J.E. Butler</i>	From <i>B.W. Griffin</i>
Co.	Co.
Dept.	Phone #
Fax #	Fax #

**ANADARKO PETROLEUM CORP.  
BRADSHAW # 2**

**SECTION 4, T-19S, R-25E  
EDDY COUNTY, NEW MEXICO**

Mud Program

**CASING:**

SURFACE: 1,300' OF 9 5/8" (12 1/4")  
PRODUCTION: 8,200' OF 5 1/2" (7 7/8")

DEPTH	MUD WEIGHT	VISCOSITY	WATER LOSS	SOLIDS	COMMENTS
0 to 400'	8.7 to 9.0	38 to 42	No Control	<4	Spud Mud
400 to 1,300'	8.4	26 to 28	No Control	<2	Fresh Water
1,300 to 6,500'	8.4	26 to 28	No Control	<1	Fresh Water
6,500 to 7,300'	8.8 to 9.0	26 to 28	No Control	<2	C/Brine
7,300 to 8,200'	8.8 to 9.2	30 to 32	10cc or less	<3	Controlled Brine My-Lo-Jel

**ESTIMATED FORMATION TOPS**

Glorietta	1,983'
Yeso	2,092'
Abo	4,300'
Wolfcamp	5,496'
Cisco	7,602'

**NOTE:**

There is a possibility of total lost circulation while drilling this interval. If this occurs and cannot be easily controlled with one to two pits of LCM (10/12 lb./bbl.) mud, it may be necessary to dry drill to total depth. If dry drilling becomes necessary, we strongly recommend viscosity sweeps be run to help keep the hole clean.



ENVIRONMENTALLY INVOLVED