to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C	101
Revised	1-1-89

DISTRIC	oen	Hobbit	МM	88240
P() HOT	PVM/	TIOUUS.	1 4148	00270

OIL CONSERVATION DIVISION P.O. Box 2088

3533' GR

DISTRICT P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27893

5. Indicate Type of Lease FEE X STATE

The Cost & Class Lagra No.

DISTRICT III 1000 Rio Brazos Rd., Aziec, N	IM 87410						6. State	ON AC CLAS DELACTO	 	77777
THE PARTY OF THE PARTY	ORY NOTICES M FOR PROPOSA ENT RESERVOIR. (FORM C-101) F	LIS TO DRILL C USE "APPLIC!	ATION FOR P	NOHFL		TO A	7. Lesse	Name or Unit Ago		(////
i. Type of Well: OLL WELL X	OAS WELL		TEX	LIAV -	7 10 1		Brad	shaw	14050	
2 Name of Operator Anadarko Petro				0. 0			2 9. Pool	name or Wildcat	66202	
PO Drawer 130 Well Location Unit Letter					Line and _	198		Feet From The	East	_ Line
Section	۸	ownship	195	Range	25E		IMPM	E	ddy c	County

	heat Ann	consiste Box to Indi	icate N	lature of Notice, Report, or	Other	r Data	
NOTICE OF INTENTION TO:			SUBSEQUENT NET OF TOTAL			-1	
PERFORM REMEDIAL WORK		PLUG AND ABANDON	_	REMEDIAL WORK		ALTERING CASING	_ _
TEMPORARILY ABANDON		CHANGE PLANS	ا سا	COMMENCE DRILLING OPNS.		PLUG AND ÁBANDONMENT	لـ
PULL OR ALTER CASING				CASING TEST AND CEMENT JO	B LXJ	· · ·	٦
OTHER:				OTHER:	ad date	of starting any proposed	

- 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
- 1. WOC @ 18 hrs surface job.
- 2. Resumed drlg 04-16-94.
- 3. Drilled to TD 8200' KB 04-29-94.
- 4. RU Schlumber & logged from TD to surface. Ran Dual Laterolog-MSFL-GR and Litho-Density-Compensated Neutron-GR Log.
- 5. Ran 201 jts (8194.24') 7" 23# M95 HC LT&C R-3 casing. Set Float Shoe @ 8198.64 KB, Float Collar @ 8161.09 & DV Tool @ 5775.73'.
- 6. RU Halliburton and cemented 1st stage w/700 sx 50/50 Premium Plus Pozmix 2/.5 of 1% Halad-9. Plug down @ 1530 hrs CDST. Opened DV Tool and circ out 103 sx cement to pit. Circ through DV Tool 6 hrs.
- 7. Cemented 2nd stage w/600 sx Halliburton Light Premium Pius w/4#/sx Flocele and 5# salt/sx and tailed in w/100 sx 50/50 Premium Plus Pozmix w/.5 of 1% Halad-9. Did not circ cement. Plug down @ 2230 hrs CDST 4-30-94.

SIGNATURE Howard Hackett Store and Complete to the best of my knowledge and bellef. The Field Foreman	DATE <u>05-11-94</u> (505) 677-2411 TELETIONE NO.
TYTE OR FRONT NAME	

(This space for State Use) SUPERVISOR, DISTRICT II

MAY 2 6 1994

CONDITIONS OF AITROVAL, IF ANY: