

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address: MARALO, INC. P. O. BOX 832 MIDLAND, TX 79702		OGRID Number 014007
Property Code 143843	Property Name STATE "11"	API Number 30-015-27916
		Well No. 1

Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	11	19S	28E		2310	SOUTH	660	EAST	EDDY

Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Proposed Pool 1 HND TURKEY TRACK (MORROW) 66352					Proposed Pool 2				

90622

Work Type Code N	Well Type Code G	Cable/Rotary R	Lease Type Code S	Ground Level Elevation 3419'
Multiple NO	Proposed Depth 11,300'	Formation MORROW	Contractor UNK.	Spud Date 05-10-94

Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17-1/2"	13-3/8"	40# & 48#	400	700 SX CL "C"	CIRC TO SURF
12-1/4"	8-5/8"	32#	2700	1100 SX HAL LT + 100 SX "C"	CIRC TO SURF
7-7/8"	5-1/2"	17#	11,300	AS REQUIRED	UNK

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. DRILL 17-1/2" HOLE TO 400±. RUN 13-3/8" CSG TO T.D. CEMENT W/ 700 SXS CLASS "C", 1/4# FLOCELE, 2% CACL. CIRCULATE CEMENT TO SURFACE.
2. DRILL 12-1/4" HOLE TO 2700±. RUN 8-5/8" CSG TO T.D. CEMENT W/ 1100 SX HALCO LT., TAIL IN W/100 SX CLASS "C", 1/4# FLOCELE, 2% CACL. CIRCULATE TO SURFACE.
3. DRILL 7-7/8" HOLE TO 11,300±. LOG WELL, RUN 5-1/2" CSG TO T.D. CEMENT TO COVER PROSPECTIVE ZONES.

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Dorothea Owens

Printed name: DOROTHEA OWENS

Title: REGULATORY

Date: 04-14-94

Phone: (915) 684-7441

OIL CONSERVATION DIVISION

Approved by:

Mark Kelly

Title: GEOLOGIST

Approval Date: 4-18-94

Expiration Date: 10-18-94

Conditions of Approval:

Attached ☐