

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-27916

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

RECEIVED

STATE "11" COM

2. Name of Operator

MARALO, INC.

8. Well No.

1

3. Address of Operator

P. O. BOX 832, MIDLAND, TX 79702

9. Pool name or Wildcat

UNDESIG. (MORROW)

4. Well Location

O. C. D.

Unit Letter I : 2310 Feet From The SOUTH ARTESIA OFFICE 660 Feet From The EAST Line

Section 11

Township 19S

Range 28E

NMPM

EDDY

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3419' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

06-25-94 THROUGH 06-30-94 DRILLING TO TD 11,300'.

07-01-94 DRILLING & LOGGING.

07-02-94 CIRC & COND HOLE FOR 5 1/2" CSG. FINISHED LOGGING W/SWSCO GR/CNL/LDT, GR/DLL, RFT. TIH TO COND HOLE FOR 5 1/2" CSG., WASHED TO BTM, CIRC & COND HOLE FOR 5 1/2" CSG.

LOGGING:	SAN ANDRES	2016'	2ND BONE SPRING CARB	7514'	ATOKA	10,204'
	BONE SPRINGS	3224'	3RD BONE SPRING SS	8360	MORROW	10,639'
	1ST BONE SPRINGS SS	6366'	WOLFCAMP	8778'	TEAL SAND	10,924'
	1ST BONE SPRING CARB	6524'	CISCO-CANYON	9534'	LOWER MORROW SHALE	11,006'
	2ND BONE SPRING SS	7202'	STRAWN	9988'	LOWER MORROW "B" SD	11,066'

07-03-94 RAN 262 JTS 5 1/2" 17# N-80 CSG. SET @ 11,300', DV TOOL @ 5243' CEMENT 1ST STAGE 5 1/2" CSG W/500 SXS HALCO LT CEMENT W/5# SALT/SX + 1/4# FLOCELE + 595 SXS 50/50 POZ MIX CEMENT W/3% KCL & 1/2% HALID 322. DROPPED BOMB & OPEN DV TOOL, CIRC THRU DV TOOL @ 5243'.

07-04-94 2ND STAGE W/310 SXS HALCO LT CEMENT W/5# SALT + 1/4# FLOCELE + 100 SXS CLASS "C" CEMENT. SET 5 1/2" CSG SLIPS, CUT OFF 5 1/2" CSG. NU WELLHEAD & RELEASED RIG. TOC ON 2ND STAGE @ 2370'. NO COMPLETION UNIT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Dorothea Owens

TITLE REGULATORY ANALYST

DATE JULY 11, 1994

TYPE OR PRINT NAME

DOROTHEA OWENS

TELEPHONE NO. (915) 684-7441

(This space for State Use)

APPROVED BY

SUPERVISOR, DISTRICT II

TITLE

DATE

JUL 29 1994

CONDITIONS OF APPROVAL, IF ANY: