NM OIL CONS COMMISSION Drawer DD Form 3160-5 UNITED STATES 882FORM APPROVED Budget Bureau No. 1004-0135 Artesia, NM (June 1990) DEPARTMENT OF THE INTERIOR Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Senal No. NM10191 SUNDRY NOTICES AND REPORTS ON WELLS SFP - 6.'94 6. If Indian, Allonee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals N/A 7. If Unit or CA, Agreement Designation ARTESIA, OFFICE SUBMIT IN TRIPLICATE 14-08-001-11572 i. Type of Well Oil Well Other 8. Well Name and No. 2. Name of Operator East Shugart Unit #54 Devon Energy Corporation (Nevada) 9. API Well No. 3. Address and Telephone No. 30-015-27948 20 N. Broadway, Suite 100, OKC, OK 405/235-3611 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Shugart (Y-SR-Q-G) Sec. 34-T18S-R31E, Unit F, 1690' FNL & 1940' FWL 11. County or Parish, State Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12: TYPE OF SUBMISSION TYPE OF ACTION → Notice of Intent Change of Plans New Construction Subsequent Report

SPUD 07-30-94 at 1830 hrs. Drilled to 954'. Ran 23 jts 8 5/8" 24# J-55 8rd csg (954'), guide shoe at 954', float collar at 897'. Cemented 8 5/8" csg with 300 sx "Lite" + 2% CaCl 2+ 1/4#/sx Celloflake, mixed at 12.7 ppg= 1.84 cf/sx yield; plus 200 sx Class C + 2% CaCl₂ mixed at 14.8 ppg= 1.32 cf/sx yield. 100 sx cement circ'd to surf. Job complete at 0247 hrs 07-31-94.

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled,

Spud and running csg

Dispose Water (Note: Report results of a

Reached TD 3924' on 08-04-94. Ran logs, DLL/MLL/GR and ZDL/CN/GR. Ran 90 jts 5 1/2" 15.5# J-55 8rd csg (2924'), shoe at 3923', float collar at 3876.90' and 25 centralizers. Preceded cement by 500 gals mud clean. Cemented with 600 sx Lite + 5# salt + 1/4#/sx Celloflake, mixed at 12.7 ppg= 1.90 cf/sx yield; plus 450 sx Class C + 3% salt + .3% FL-62 + 1/4#/sx Celloflake, mixed at 14.8 ppg= 1.32 cf/sx yield. 81 sx cement circ'd to surf. job complete at 1818 hrs 08-05-94.

Released rig at 2100 hrs 08-05-94. Waiting on completion.

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Final Abandonment Notice

14. I hereby certify that the foregoing is true and correct Signed Cancace R. Graham	Title _	Candace R. Graham Engineering Tech.	Date <u>8-8-94</u>
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title		Date
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly or representations as to any matter within its jurisdiction.	aad willfu	illy to make to any department or agency of the Ur	nited States any false firtinger or foundations