Form 3160-5 (June 1990)

Released Rig @ 2045 hrs 10/18/95. WOCU.

14. I hereby ceptify that the foregoing is true and correct

(This space for Federal or State office use)

UNIT STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OIL CONSERVATION DIV d11 S. 1st ST. ARTESIA, NM 88210-2834

| | 1995

W MEXICO

c158

BUREAU OF LAND MANAGEMENT FORM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. NM(10190) 10 191 Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas Well ⊠ Oil Well ☐ Other 14-08-001-11572 8. Well Name and No. 2. Name of Operator **DEVON ENERGY GORPORATION (NEVADA)** East Shugart Unit #56 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 30-015-27949 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 2250' FNL and 1910' FEL of Section 35-17S-31E. Unit letter "G" Shugart (Y-SR-Q-G) 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud, TD & csg strings Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud on 10/10/95 @ 1645 hrs, Drld 12-1/4" hole to 950'. On 10/11/95, Ran 23 jts of 8-5/8" 24# J-55 8rd LT&C, shoe set @ 949'. (FC @ 911', 4 centralizers) Dowell Schlumberger Cmt'd as follows: Lead w/300 sxs lite w/2% CaCl2 + 1/4 pps celloflake, tail w/200 sxs cl "C" w/2% CaCl2. 81 sxs cmt returned to surface Drld 7-7/8" hole. Reached TD of 4073' on 10/17/95 @ 1930 hrs. Western Ran DLL/MLT/GR and ZDL/CN/GR/logs. On 10/18/95, Ran 97 jts 5-1/2" 15.5# J-55 8rd LT&C csg, shoe set @ 4072' (FC @ 4099', 19 centralizers). Dowell Schlumberger Cmt'd as follows: Lead w/600 sxs lite (5 pps salt, 1/4 pps flocele) Tail w/450 sxs cl "C" (w/3% salt + .4% D58 + .2% D65 disp + 1/4 pps celloflake) 82 sxs cmt returned to surface.

Approved by Title Date Conditions of approval, if any:

Diana Keys
Title Engineering Technician