

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION

Artesia, NM 88210
Drawer DD

RECEIVED

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241 (505) 393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FWL & 1650' FNL

Sec. 26-T20S-R25E

5. Lease Designation and Serial No.

NM-88098

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. Bubbling
Springs "26" Fed. #1

9. API Well No.

30-015-27997

10. Field and Pool, or Exploratory Area

West Bubbling
Springs Morrow

11. County or Parish, State

Eddy Co., N.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Cement 9-5/8" Int.
Casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

07/25/94 Drilled 12-1/4" Intermediate hole to 2,496' KB. Ran 58 jts. of new LS, 9-5/8", 40# & 36#, 8rd, LT&C & ST&C casing. Set @ 2,496' KB. Halliburton cemented w/ 500 sacks of Class "C" Lite containing 1/2#/sk. flocele + 5#/sk. Gilsonite + 2% CaCl2 followed by 200 sacks of Class "C" neet containing 3% CaCl2. Plug down to 2,450' @ 3:00 p.m., 07/25/94. Circulated 71 sacks of cement to the pit. WOC 12 hours and NU BOP's. Pressure tested casing, wellhead, and BOP's to 1,200# for 30 minutes. All held ok.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Drilling Superintendent

Date

07/29/94

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side