

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

## 1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

## 2. Name of Operator

Mewbourne Oil Company

## 3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241 (505) 393-5905

## 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FWL & 1650' FNL  
Sec. 26-T20S-R25E

## 7. If Unit or CA, Agreement Designation

8. Well Name and No.  
Bubbling Springs "26"

## 9. API Well No.

30-015-27997

## 10. Field and Pool, or Exploratory Area

West Bubbling Springs

## 11. County or Parish, State

Eddy County, N.M.

## 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

## TYPE OF ACTION

☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

08/20/94 Drilled 8-3/4" production hole to 10,031' KB. Ran E-logs & evaluated same. Decided to plug well. Received verbal plugging orders from Adam Salameh with Carlsbad BLM office. Plugged well in following manner:

- Spotted Class "H" plug from 9,550'-9,350' (90 sacks)
- Spotted Class "H" plug from 7,200'-7,050' (80 sacks)
- Spotted Class "H" plug from 4,650'-4,500' (60 sacks)
- Spotted Class "H" plug from 2,550'-2,450' (55 sacks)
- Spotted Class "H" plug from 300'-200' (35 sacks)

Part ID-2  
11-11-94  
PVA

Waited on plug to set up and tagged @ 196'. Spotted Class "H" plug @ 50'-0' (20 sacks). Cut off wellhead, welded on plate and installed dry hole marker w/proper inscription. Released rig @ 5:00 P.M. 08/21/94.

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

## 14. I hereby certify that the foregoing is true and correct

Signed Red Prince Title Drilling Superintendent Date August 25, 1994

(This space for Federal or State office use)

Approved by Orig. Signed by Shannon J. Shaw  
Conditions of approval, if any:Title Petroleum Engineer Date 9/30/94