

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION

Drawer DD

Artesia, NM 88210  
FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals **RECEIVED**

SUBMIT IN TRIPLICATE

AUG 04 '94

Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1400 ARTESIA, OFFICE

Address and Telephone No.

105 South 4th St., Artesia, NM 88210

Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FEL of Section 31-T19S-R24E (Unit H, SENE)

5. Lease Designation and Serial No.

NM-76936

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sunflower AHW Federal #3

9. API Well No.

30-015-28027

10. Field and Pool, or Exploratory Area

Wildcat Abo

11. County or Parish, State

Eddy Co., NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Surface casing & cement  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8 5/8", 24" (SJS)  
Reduced hole to 12-1/4" at 383'. Drilled to 1410'. Reached TD of 1410' at 7:00 AM 7-16-94. Ran 32 joints of 13 3/8" 54.5# J-55 (1413.95') of casing set at 1410'. 1-Texas Pattern notched guide shoe set at 1410'. Insert float set at 1365'. Cemented with 200 sacks Class H, 12% Thixad, 18#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl2 (yield 1.66, weight 14.1) and 850 sacks Pacesetter Lite "C", 10#/sack gilsonite, 1/2#/sack celloseal and 3% CaCl2 (yield 1.98, weight 12.46). Tailed in with 250 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 2:00 PM 7-16-94. Bumped plug to 1150 psi. Float did not hold. Circulated 75 sacks to pit. WOC. Drilled out at 11:45 AM 7-17-94. WOC 21 hours and 45 minutes. Nipped up and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling. NOTE: Notified BLM in Carlsbad - did not witness. Float did not hold - left shut in for 4 hours.

4. I hereby certify that the foregoing is true and correct

Signed Rusty Klein Title Production Clerk

Date July 20, 1994

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_ Date \_\_\_\_\_

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side