

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-28033

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil
WELL ☒

GAS
WELL ☐

OTHER

NOV 22 1994

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line

Section 28

Township 19S

Range 25E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3483' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate & acidize ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-15-94 - Cleaned location and set anchors. Moved in and rigged up pulling unit.

11-16-94 - Nippled up BOP. TIH with bit, stabilizer, drill collars and 2-7/8" tubing.

Drilled out DV tool at 5960'. Tested to 1500 psi. TIH and tagged PBTD at 8155'. Displaced hole with 2% KCL. TOOH. Laid down drill collars. TIH with bit and scraper to 6000'. TOOH. Rigged up wireline and ran GR/CBL log.

11-17-94 - Rigged up wireline. TIH with 4" casing guns and perforated 7780-7788' w/10 .42" holes. TOOH with wireline. TIH with 7" Uni V packer on 2-7/8" tubing. Spotted 2 bbls 20% NEFE acid at 7788'. Pulled up and pumped 2 bbls water down annulus. No circulation. Set packer and loaded tubing with 6 bbls. Acidized perforations 7780-7788' w/1500 gallons 20% NEFE acid. Swabbing.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Clerk

DATE 11-17-94

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

DEC 8 1994