

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUG BACK, OR ADD A ZONE

Operator Name and Address. YATES PETROLEUM CORPORATION 105 South Fourth Street Artesia, New Mexico 88210		OGRID Number 025575	
Property Code 154104		Property Name STATE K	
Well No. #4		API Number 30-015-28103	
SEP 15 '94		O.C.D. ARTESIA, OFFICE	

7 Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	28	19S	25E		1980'	South	660'	West	Eddy

8 Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Proposed Pool 1 N. Dagger Draw Upper Penn					15472	Proposed Pool 2 N/A			

Work Type Code N	Well Type Code O	Cable/Rotary R	Lease Type Code S	Ground Level Elevation 3492'
Multiple No	Proposed Depth 8200'	Formation Canyon	Contractor Not Determined	Spud Date ASAP

21 Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
14 3/4"	9 5/8"	36# J-55	1150'	1100 sx.	Circulated
8 3/4"	7"	23#, 26#	TD	1350 sx.	Post ID-1
		J-55, N-80			9-23-94
					New Log & API

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

YATES PETROLEUM CORPORATION PROPOSES TO DRILL AND TEST THE CANYON AND INTERMEDIATE FORMATIONS. APPROXIMATELY 1150' OF SURFACE CASING WILL BE SET AND CEMENT CIRCULATED TO SHUT OFF GRAVEL AND CAVINGS. IF COMMERCIAL, PRODUCTION CASING WILL BE RUN AND CEMENTED, WILL PERFORATE AND STIMULATE AS NEEDED FOR PRODUCTION.

MUD PROGRAM: FW gel/LCM to 1150'; FW to 5200'; Cut Brine/KCL to 7200'; Cut Brine/KCL/Starch to TD.

BOP PROGRAM: BOP's and hydril will be installed on the 9 5/8" casing and tested daily.

TIME TO WITNESS CEMENTING THE CASING

I hereby certify that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Ken Beardemphl</i>		OIL CONSERVATION DIVISION Approved by: <i>Mark Kelly</i>	
Printed name: KEN BEARDEMPHL		Title: GEOLOGIST	
Title: LANDMAN		Approval Date: 9-16-94	
Date: 9/13/94		Expiration Date: 3-16-95	
Phone: 748-4347		Conditions of Approval: Attached <input type="checkbox"/>	