ubmit 3 Copies Appropriate Sistrict Office	State of New Me En Minerals and Natural Re		Form C-103 Revised 1-1-89
istrict Office <u>ISTRICT I</u> .O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION P.O. Box 2088		WELL API NO. 30-015-28103
ISTRICT II O. Drawer DD, Antesia, NM 88210 Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease STATE X FEE	
USTRICT III 000 Rio Brazos Rd., Aztec, NM 8741	0		6. State Oil & Gas Lease No. K-6096
DIFFERENT AS	DTICES AND REPORTS ON WEL PROPOSALS TO DRILL OR TO DEEPEN SERVOIR. USE "APPLICATION FOR PE M C-101) FOR SUCH PROPOSALS.)	OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
Type of Well:			
WELL X WELL	OTHER ()		State K
Name of Operator YATES PETROLEUM CORP	ORATION 22	RECENTED B	4
Address of Operator		DCD - Artenie - A	9. Pool name or Wildcat
105 South 4th St., A	rtesia, NM 88210	JUU - KELENIA - JU	Dagger Draw Upper Penn, North
. Well Location			
Unit Letter L :;	1980 Feet From The South	Line and <u>6</u>	60 Feet From The <u>West</u> Line
	100	ange 25E	NMPM Eddy County
Section 28	Township 19S R.		
	3492'		
Cha	ck Appropriate Box to Indicate		Report, or Other Data
	INTENTION TO:	I SUE	BSEQUENT REPORT OF
NOTICE OF			—
		REMEDIAL WORK	
		1	
EMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLIN	
г <del></del>	CHANGE PLANS	COMMENCE DRILLIN	
ULL OR ALTER CASING	]	CASING TEST AND C OTHER: Perforat	EMENT JOB
ULL OR ALTER CASING THER: 12. Describe Proposed or Completed O work) SEE RULE 1103. 10-1-97 - Cleaned J 10-2-97 - Moved in psi. TIH with bit, ulated casing clean to PBTD of 9508'. with logging tools 10-3-97 - Finished guns and perforated 9223-9227' (4 SPF packer, on/off too wellhead. Set pack Acidized perforati scf/bbl N2 and bal 10-4-6-97 - Flow t 10-8-97 - POOH witt I hereby certify that the information above SKONATURE	Derations (Clearly state all periment details, of location, set and tested and rigged up pulling un drill collars and 2-7/8 h and tested casing to 27 Displaced casing with 27 and run CBL/CCL/GR logs running CBL/CCL/GR log. d 9203-9227' w/56 .41" ho - Morrow). TOOH with cas 1, 2.25" profile nipple ker at 9143'. Swabbed d ons 9203-9227' with 1500 1 sealers. Opened well esting. Shut well in. h 72 hour BHP bombs. We	CASING TEST AND C OTHER: Perforat and give periment dates, incl anchors. hit. Installed 3" tubing. Dri 100 psi. TOOH. % KCL water. To TOOH with log oles as follows sing guns and r and 2-7/8" tubi own. Kicked of gallons 7-1/2% up and flow tes TIH with 72 hou	EMENT JOB The & acidize [X] The & acidize [X] The diagent estimated date of starting any proposed BOP and tested casing to 1800 Iled out DV tool at 6501'. Circ- TIH with bit, scraper and tubing OOH. Rigged up wireline. TIH ging tools. TIH with 4" casing : 9203-9206', 9210-9214' and igged down wireline. TIH with ng. Removed BOP and nippled up f flowing. Installed treesaver. iron control HCL acid with 1000 ting. r BHP bombs.
ULL OR ALTER CASING THER: 12. Describe Proposed or Completed O work) SEE RULE 1103. 10-1-97 - Cleaned J 10-2-97 - Moved in psi. TIH with bit; ulated casing clean to PBTD of 9508'. with logging tools 10-3-97 - Finished guns and perforated 9223-9227' (4 SPF packer, on/off too wellhead. Set pack Acidized perforati scf/bbl N2 and bal 10-4-6-97 - Flow t 10-8-97 - POOH witt I hereby certify that the information above SKONATURE	Derations (Clearly state all periment details, of location, set and tested and rigged up pulling un drill collars and 2-7/8 h and tested casing to 27 Displaced casing with 27 and run CBL/CCL/GR logs running CBL/CCL/GR log. d 9203-9227' w/56 .41" ho - Morrow). TOOH with cas 1, 2.25" profile nipple ker at 9143'. Swabbed d ons 9203-9227' with 1500 1 sealers. Opened well esting. Shut well in. h 72 hour BHP bombs. We	CASING TEST AND C OTHER: Perforat and give periment dates, incl anchors. hit. Installed "tubing. Dri 100 psi. TOOH. KCL water. To TOOH with log oles as follows sing guns and r and 2-7/8" tubi own. Kicked of gallons 7-1/2% up and flow tes TIH with 72 hou at belief.	EMENT JOB The & acidize [X] The & acidize [X] The diagenergy proposed BOP and tested casing to 1800 11ed out DV tool at 6501'. Circ- TIH with bit, scraper and tubin 00H. Rigged up wireline. TIH ging tools. TIH with 4" casing : 9203-9206', 9210-9214' and igged down wireline. TIH with ng. Removed BOP and nippled up f flowing. Installed treesaver. iron control HCL acid with 1000 ting. TELEPHONE NO. 505/748-14 I
ULL OR ALTER CASING THER: 12. Describe Proposed or Completed O work) SEE RULE 1103. 10-1-97 - Cleaned J 10-2-97 - Moved in psi. TIH with bit, ulated casing clean to PBTD of 9508'. with logging tools 10-3-97 - Finished guns and perforated 9223-9227' (4 SPF packer, on/off too wellhead. Set pack Acidized perforati scf/bbl N2 and bal 10-4-6-97 - Flow t 10-8-97 - POOH with Incredy certify that the information above SKONATURE TYPE OR PRINT NAME Rusty K.	Derations (Clearly state all periment details, of location, set and tested and rigged up pulling un drill collars and 2-7/8 h and tested casing to 27 Displaced casing with 27 and run CBL/CCL/GR logs running CBL/CCL/GR log. d 9203-9227' w/56 .41" ho - Morrow). TOOH with cas 1, 2.25" profile nipple ker at 9143'. Swabbed d ons 9203-9227' with 1500 1 sealers. Opened well esting. Shut well in. h 72 hour BHP bombs. We	CASING TEST AND C OTHER: Perforat and give periment dates, incl anchors. hit. Installed "tubing. Dri 100 psi. TOOH. KCL water. To TOOH with log oles as follows sing guns and r and 2-7/8" tubi own. Kicked of gallons 7-1/2% up and flow tes TIH with 72 hou at belief.	EMENT JOB X   te & acidize X   uding estimated date of starting any proposed X   BOP and tested casing to 1800 11ed out DV tool at 6501'. Circ- TIH with bit, scraper and tubing   OOH. Rigged up wireline. TIH   ging tools. TIH with 4" casing   : 9203-9206', 9210-9214' and   igged down wireline. TIH with   ng. Removed BOP and nippled up   f flowing. Installed treesaver.   iron control HCL acid with 1000   ting.   TEchnician   DATE Oct. 15, 1997

,