

RECEIVED  
APR 5 10 43 AM '95

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

NM OIL CONS COMMISSION  
Drawer DD  
Artesia

FORM APPROVED  
Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-0557142

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ross EG Federal Com #13

9. API Well No.

30-015-28128

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn, North

11. County or Parish, State

Eddy Co., NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FEL of Section 20-T19S-R25E (Unit I, NESE)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud, resume drilling, surface casing & cement

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 26" hole with rat hole machine at 11:00 AM 3-25-95. Set 73' of 20" conductor pipe. Cemented to surface. NOTE: Notified BLM answering service of spud.

Resumed drilling a 14-3/4" hole with rotary tools at 7:15 PM 3-27-95. Reached TD at 7:15 AM 3-29-95. Ran 26 joints of 9-5/8" 40# J-55 (1156.51') of casing set at 1155'. Pattern notched guide shoe set at 1155'. Insert float set at 1110'. Cemented with 200 sacks Class "H", 12% thixad, 10#/sack gilsonite, 1/2#/sack celloseal and 2% CaCl2 (yield 1.56, weight 14.6) and 900 sacks Pacesetter Lite C, 6% gel, 10#/sack gilsonite, 1/2#/sack celloseal and 3% CaCl2 (yield 2.01, weight 12.4). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 6:57 PM 3-29-95. Bumped plug to 1000 psi, float did not hold. Cement did not circulate. WOC 4-1/4 hours. Ran Temperature Survey and found top of cement at 110'. Ran 1". Tagged cement at 118'. Spotted 200 sacks Class C 3% CaCl2. PD 12:45 AM 3-30-95. WOC 1 hour. Ran 1". Tagged cement at 78'. Spotted 100 sacks Class C 3% CaCl2. PD 1:50 AM 3-30-95. Circulated 10 sacks to pit. WOC. Drilled out at 8:00 PM 3-30-95. WOC 25 hours and 3 minutes. Nippled up and tested to 1000 psi for 15 minutes. Cut off and weld on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

*Rustyn Klein*

Title Production Clerk

Date April 3, 1995

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

*J. Lara*  
3 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side

CARLSBAD, NEW