YATES PETROLEUM CORPORATION Ross EG Federal Com #13 Section 20-T19S-R25E Eddy County, New Mexico

#32: ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.:

. —

TREATMENT

DEPTH INTERVAL	TREATMENT	
7800-7806'	Spot 3 bbls acid - communicated	
7756-7806'	Acidized with 300 gallons 20% NEFE acid - communicated	
7654-7728'	Acidized with 3000 gallons 20% NEFE acid	
7654-7780'	Acidized with 25000 gallons 20% gelled acid	
7744'	Cement retainer set	
7756-7780'	Squeezed with 150 sacks Class H, .8% fluid loss, .3% thriftylite (yield 1.18, weight 15.6), 100 sacks "H", 12% thixad, 2#/sack hiseal (yield 1.43, weight 15.8) and 150 sacks "H", .8% flud loss and .3% thriftylite (yield 1.18, weight 15.6) with 36 bbls displacement	
7550 '	Cement retainer set - drilled out	
7654-7728'	Squeezed with 100 sacks "H", .8% fluid loss, .3% thriftylite (yield 1.18, weight 15.7), 100 sacks "H", 12% thixad (yield 1.43, weight 15.6) and 150 sacks "H" Neat (yield 1.18, weight 15.6). Perfs squeezed with 150 sacks in formation.	
7705 '	sand jet cut – break down – communicated – pumped 3 bbls acid	
7697'	sand jet cut - communicated	
7683'	sand jet cut - communicated - pumped 10-1/2 bbls	
7666'	sand jet cut - pumped 12-1/2 bbls - communicated	
7656'	sand jet cut - pumped 26-1/2 bbls	
7656-7705'	Acidized with 15000 gallons 20% NEFE gelled acid with rock salt	
7654-7728'	Acidized (via 7" casing) with 40000 gallons crosslink gelled acid. Flushed with 53000 gallons treated KCL water	





Job separation sheet



·	
WELL	Ross "EG" Federal Com #13
LOCATION	Sec. 20-19S-25E, Eddy County, New Mexico
OPERATOR	<u>Yates Petroleum Corporation</u> 207 S. 4th Street Artesia, New Mexico 88210
DRILLING CONTRACTOR	Exeter Drilling Company

The undersigned hereby certifies that he is an authorized representative of the drilling contractor who drilled the above described well and that he has conducted deviation tests and obtained the following results:

Degrees @ Depth	Degrees (a) Depth	Degrees (a) Depth
1 1/4 235	1 1/4 8,300	
1 1/4 500	<u> </u>	
1 3/4 1,018		
1 1/2 1,155		
1 1,630		
3/4 2,130		
3/4 2,630		
1/2 3,130		
1/4 3,625		
1/2 4,125		_,
1 1/4 4,622		
1 1/4 4,930		
1 3/4 5,180		
1 3/4 5,430		
2 1/4 5,715		······································
2 6,210		
2 1/4 6,700		
1 3/4 7,200		
3/4 7,526		

Drilling Contractor: EXETER DRILLING COMPANY

Bob Lange By:

Drilling Manager Southern Division

Subscribed and sworn before me this 20th day of April, 1995.



Daphne R. Watson Unte

Daphne R. Watson Notary Public Commission Expires: March 22, 1997