

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. NM-1372
2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., of Survey Description) 660' FSL & 660' FWL of Section 9-T19S-R25E (Unit M, SWSW)	8. Well Name and No. Warren ANW Federal #2
	9. API Well No. 30-015-28147
	10. Field and Pool, or Exploratory Area North Dagger Draw Upper Penn
	11. County or Parish, State Eddy Co., NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other Resume drilling, surface casing & cement	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Resumed drilling a 14-3/4" hole with rotary tools at 3:45 PM 11-14-94.

TD 1108'. Ran 25 joints of 9-5/8" 36# J-55 ST&C 8rd (1111') of casing set at 1108'. 1-Texas Pattern notched guide shoe set at 1108'. Float collar set at 1064'. Cemented with 900 sacks Pacesetter Lite C, 10#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl<sub>2</sub> (yield 1.99, weight 12.4). Tailed in with 200 sacks Class C 2% CaCl<sub>2</sub> (yield 1.32, weight 14.8). PD 1:30 AM 11-16-94. Bumped plug to 750 psi, OK. Circulated 150 sacks cement. WOC. Drilled out at 5:00 AM 11-17-94. WOC 27 hours and 30 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Tested casing to 1000# for 30 minutes, OK.

14. I hereby certify that the foregoing is true and correct		
Signed <u>Rusty Klein</u>	Title <u>Production Clerk</u>	Date <u>Nov. 18, 1994</u>
(This space for Federal or State office use)		
Approved by _____	Title _____	Date _____
Conditions of approval, if any:		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side