orm 3160-5 me 1990)

UNIT ... STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Dr	. 8	WESTORM	APPROVED
Ar	ŧ,	Budget Bure Expires:	March 31, 1993

NM OIL CONS COMMISSION

5. Lease Designation and Serial No.

NM.	1	2	7	2

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE J:11 70 25 1. Type of Well X Well 8. Well Name and No. L. Other 2. Name of Operator Warren ANW Federal #2 (505) 748-1471)9. API Well No. YATES PETROLEUM CORPORATION 3. Address and Telephone No. 30-015-28147 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) North Dagger Draw Upper Penn 660' FSL & 660' FWL of Section 9-T19S-R25E (Unit M, SWSW) 11. County or Parish, State Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment New Construction Recompletion Subsequent Report Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Altering Casing Conversion to Injection Final Abandonment Notice Other Production casing & cmt Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* TD 8260'. Reached TD at 2:15 AM 12-5-94. Ran 202 joints of 7" 26# & 23# casing as follows: 16 joints of 7" 26# N-80 sandblasted (643.27'); 64 joints of 7" 26# J-55 varnished (2592.20'); 90 joints of 7" 23# J-55 varnished (3742.47'); 32 joints of 7" 26# J-55 varnished (1282.93') (Total 8260.77') of casing set at 8260'. Float shoe set at 8260'. Float collar set at 8218.85'. DV tool set at 6004.43'. Cemented in two stages as follows: Stage 1: 450 sacks Super C (65-15-11), .5% CF-2, .4% CF-14, 3.42#/sack salt and 8#/sack Hiseal (yield 1.76, weight 13.0). PD 5:15 AM 12-7-94. Bumped plug to 1400 psi for 1 minute. Circulated 50 sacks. Circulated through DV tool for 2-1/4 hours. Stage 2: 800 sacks Pacesetter Lite C (65-35-6), 5#/sack salt and 5#/sack gilsonite (yield 1.99, weight 12.45). Tailed in with 100 sacks Class H Neat (yield 1.18, weight 15.6). PD 9:15 AM 12-7-94. Bumped plug to 3100 psi for 1 minute, OK. Circulated 175 sacks. Released rig at 1:00 PM 12-7-94. Waiting on completion unit. DI CQ! 14. I hereby certify that the foregoing Dec. 9, 1994 Production Clerk Title Approved by _______ Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.