

1-05  
District I  
PO Box 1980, Hobbs, NM 88241-1980  
District II  
PO Drawer DD, Artesia, NM 88211-0719  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico  
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION  
PO Box 2088  
Santa Fe, NM 87504-2088

Form C-101  
Revised February 10, 1994  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 6 Copies  
Fee Lease - 5 Copies

OCT - 3 '94

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPE~~N~~, PLUGBACK, OR ADD A ZONE

Operator Name and Address. YATES PETROLEUM CORPORATION 105 South Fourth Street Artesia, New Mexico 88210		ARTESIA, OFFICE	' OGRID Number 025575
			' API Number 30 - 015-28150
' Property Code 15289	' Property Name NEARBURG K		#1 ' Well No.

7 Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	28	19S	25E		1650'	South	990'	East	Eddy

8 Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
' Proposed Pool 1 N. Dagger Draw Upper Penn					15472				
					N/A				

' Work Type Code N	' Well Type Code O	' Cable/Rotary R	' Lease Type Code S	' Ground Level Elevation 3472'
' Multiple No	' Proposed Depth 8200'	' Formation Canyon	' Contractor Not Determined	' Spud Date ASAP

21 Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
14 3/4"	9 5/8"	36# J-55	1150'	1100 sx.	Circulated
8 3/4"	7"	23#, 26#	TD	1350 sx	Post FO-1
		J-55, N-80			10-14-94
					New Log & RPF

12 Describe the proposed program. If this application is to DEEPE~~N~~ or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

YATES PETROLEUM CORPORATION PROPOSES TO DRILL AND TEST THE CANYON AND INTERMEDIATE FORMATIONS. APPROXIMATELY 1150' OF SURFACE CASING WILL BE SET AND CEMENT CIRCULATED TO SHUT OFF GRAVEL AND CAVINGS. IF COMMERCIAL, PRODUCTION CASING WILL BE RUN AND CEMENTED, WILL PERFORATE AND STIMULATE AS NEEDED FOR PRODUCTION.

MUD PROGRAM: FW gel/LCM to 1150'; FW to 5200'; Cut Brine/KCL to 7200'; Cut Brine/KCL/Starch to TD.

BOP PROGRAM: BOP's and hydril will be installed on the 9 5/8" casing and tested daily.

NOTIFY N.M.O.G.D. IN SUFFICIENT  
TIME TO WITNESS CEMENTING THE  
CASING

13 I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Printed name:

KEN BEARDEMPHL

Title:

LANDMAN

Date:

10/3/94

Phone:

848-4348

OIL CONSERVATION DIVISION

Approved by:

Title:

GEOLOGIST

Approval Date:

10-7-94

Expiration Date:

4-7-95

Conditions of Approval:

Attached ☐