m 3160-5 1e 1990)	UNITED DEPARTMEN', [THE INTERIOR	Drawer	מס	FORM APPROVED MISSION o. 1004-0135 Expires: March 31, 1993 Prog enation and Serial No.	CISF
	BUREAU OF LANI	MANAGEMENT RECEL	VED ^{Artesia}	, NM 1982	NM-76936	
)o not use this	SUNDRY NOTICES AND form for proposals to drill or Use "APPLICATION FOR PE	REPORTS ON WELLS to deepen or reentry to a diff	ferent reservoir	6. If Indi	an, Allottee or Tribe Name	
F84, ~~ -	SUBMIT IN		: :5	7. If Uni	t or CA, Agreement Designation	
Type of Well S Oil Gas Well Well				8. Well N	ame and No.	
Name of Operator			71)	Sunfl 9. API W	ower AHW Federal	#5
	OLEUM CORPORATION	(505) 748-14	/1)		n - 015 - 28160	
Address and Telephone 105 South	4th St., Artesia, NM 8	8210			and Pool, or Exploratory Area	
Location of Well (Foo	tage Sec T R. M. or Survey Descripti	on)		<u>Sie</u>	grest Draw Abo	
1830' FSL 8	2000' FEL of Section	31-T19S-R24E (Unit J,	NWSE)	e	ty or Parish, State Eddy Co., NM	· · · ·
CHECK	APPROPRIATE BOX(s) T) INDICATE NATURE OF I	NOTICE, REP	ORT, OR	OTHER DATA	
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO						
		Abandonment		C Ct	lange of Plans	
I Notic	e of Intent			<u>ر</u> م	ew Construction	
X Subse	quent Report	Plugging Back		Ē	on-Routine Fracturing ater Shut-Off	
		Casing Repair		r1	ater Shut-Off	
L Final	Abandonment Notice	X Other Surface	casing & ce	ment 🗌 D	ispose Water Report results of multiple completion on	Well
				Comple	tion or Recompletion Report and Log fo	orm.)
give subsurface	Completed Operations (Clearly state all perti- locations and measured and true vertical dep	the for all markers and zones periment to u	us work.)			inneo,
TD 1406'. J-55 ST&C (Pattern not sacks "H", yield 1.55) 3% CaCl2 (y weight 14.8 WOC 4-1/4 H cement at 2 1". Tagged hours. Rat 10-22-94. WOC 29 hout hole to 7-2	Reached TD at 5:45 AM (1392.85') of casing la ched guide shoe set at 12% Thixad, 1/4#/sack and 800 sacks Paceset yield 2.01, weight 12.4 3). PD 1:15 PM 10-22-9 hours. Ran Temperature 280'. Spotted 75 sacks d cement at 270'. Spot 1". Tagged cement at Cement circulated 10 s cs and 45 minutes. Nig 7/8". Resumed drilling Did not witness.	10-22-94 (12-1/4" hole nded at 1406'. NOTE: 1406'. Insert float celloseal, 18#/sack gi ter Lite "C", 1/4#/sac). Tailed in with 250 4. Bumped plug to 750 Survey and found top "C" 4% CaCl2. PD 7:3 ted 50 sacks "C" 4% Ca 210'. Spotted 315 sa acks to surface. WOC.	<pre>). Ran 32 Had 17' 1a set at 1362 lsonite and k celloseal sacks Clas psi, OK. of cement a 0 PM 10-22- Cl2. PD 9: cks "C" 3% Drilled o 1500# for 1</pre>	nding jo .98'. C 2% CaCl , 10#/sa s C 2% C Cement d t 200'. 94. WOC 15 PM 10 CaCl2. ut at 7: 0 minute	int. 1-Texas emented with 200 2 (weight 15.6, ck gilsonite and aC12 (yield 1.32 id not circulate Ran 1". Tagged 1-1/2 hour. Ra -22-94. WOC 1-1 PD 12:00 midnigh 00 PM 10-23-94. s, OK. Reduced	• /2 t
4. I hereby certify that	the foregoing is true and correct	Due bestien 0	1		CERTED SEORIRE4	••••
Signed 7	Illy / flln			; Ť		
•	ral dy State office use)	The second s		; , r	Date <u>NOV 6.199</u> /1	
Approved by Conditions of approv	val, if any:	Title			10	
		······································		c	ARI SRAD NEW MA	
Title 18 U.S.C. Section or representations as to	1001, makes it a crime for any person know any matter within its jurisdiction.	ringly and willfully to make to any departme	ent or agency of the U	nited States inv	false nettions or traudulent sta	tements

.

*See Instruction on Reverse Side