

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Drawer DD  
Ar ia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.  
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage. Sec., T., R., M., or Survey Description)  
1650' FSL & 1150' FWL, Sec. L-35-18S-31E

5. Lease Designation and Serial No.  
NM10190

6. If Indian, Allottee or Tribe Name  
N/A

7. If Unit or CA, Agreement Designation  
14-08-001-11572

8. Well Name and No.  
East Shugart Unit #72

9. API Well No.  
30-015-28203

10. Field and Pool, or Exploratory Area  
Shugart (Y-SR-Q-G)

11. County or Parish, State  
Eddy, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other Spud and setting csg strings
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

SPUD 01-18-95 at 1630 hrs. Drilled 12 1/4" hole to 950'.

On 01-19-95 ran 24 jts 8 5/8" 24# J-55 8rd ST&C surface csg (956.40') w/guide shoe set at 949', float collar at 894' and 4 centralizers. Dowell cemented 8 5/8" csg as follows: 300 sxs lite w 2% CaCl<sub>2</sub> and 1/4 #/sx Celloflakes, mixed at 12.7 ppg = 1.93 cf/sx yield; + 200 sxs Class C w/2% CaCl<sub>2</sub>, mixed at 14.8 ppg = 1.32 cf/sx yield; circ'd 136 sx to surface. Job complete at 1945 hrs 01-19-95.

Drilled 7 7/8" hole to 4040'. Reached TD 01-24-95. Atlas ran DLL/MLL/GR/C and ZNL/CN/GR/C logs.

On 01-25-95 ran 95 jts 5 1/2" 15.5# J-55 8rd production casing (4061.76') w/float shoe set at 4039', float collar at 3985' and 20 centralizers. Dowell cemented 5 1/2" csg as follows: 550 sx Lite w/5#/sx salt and 1/4#/sx Celloflakes, mixed at 12.8 ppg = 1.98 cf/sx yield; + 600 sxs Class C w/3% salt, .4% D-59 (FL), .2% D-65 (Dispersant) and 1/4#/sx Celloflakes, mixed at 14.8 ppg = 1.35 cf/sx yield; circ'd 170 sxs cement to surface. Job complete at 1435 hrs 01-25-95.

Waiting on completion.

14. I hereby certify that the foregoing is true and correct

Signed Candace R. Graham

CANDACE R. GRAHAM  
ENGINEERING TECH.

Date 2/2/95

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

ACCEPTED FOR RECORD

Date 2/8/95

CARLSBAD, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side