

30-015-28269

Operator <u>Gates Petr. Corp</u>		Lease <u>Boyd X State</u>		Well # <u>5</u>	
Location of Well	Unit <u>I</u>	Section <u>29</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>NA</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
14 3/4	* 9 5/8	36 # J-55		1150	1100 Circ
8 3/4	7	23 # J-55		8300 TD	1350
		26 # N-80			

Casing Data:

Surface _____ joints of 9 5/8" inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date 11-1-95

Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required _____Type of Shoe used guide Float collar used inset Btm 3 jts welded yesTD of hole 1165' Set 1165' Feet of 9 5/8" Inch 36 # Grade J-55(New) used csg. @ 1165' with 200 2% sacks neat cement around shoe+ 900 sax P/L-C additives 10# gilsonite, 1/4# celocel, 2% orePlug down @ 7:15 (AM) (PM) Date 11-2-95Cement circulated yes No. of Sacks 199 58Cemented by Halliburton Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

L.O.B. - 980'

14 3/4" hole R.T. - 38 hrs