

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION

PO Box 2088
Santa Fe, NM 87504-2088

RECEIVED

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

OIL CON. DIV.

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUG BACK, OR ADD A ZONE

Operator Name and Address: YATES PETROLEUM CORP. 105 South Fourth Street Artesia, New Mexico 88210		OGRID Number 025575
Property Code 16482	Property Name Aparejo "APA" State Com.	API Number 30-015-28327
		Well No. 1

Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	16	19S	25E		660'	North	660'	West	Eddy

Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Proposed Pool 1 Dagger Draw Upper Penn North 15472					Proposed Pool 2				

Work Type Code N	Well Type Code O	Cable/Rotary R	Lease Type Code S	Ground Level Elevation 3517
Multiple No	Proposed Depth 8350'	Formation Canyon	Contractor Not Determined	Spud Date ASAP

Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
14 3/4"	9 5/8"	36# -J-55	1150'	1100 sx	Circulated
8 3/4"	7"	23# & 26#	TD	1350 sx	W
		J-55 & N-80			

Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Yates Petroleum Corporation wishes to drill and test the Canyon and intermediate formations. Approximately 1150' of surface casing will be set and cement circulated to shut off gravel and cavings. If commercial, production casing will be run and cemented, will perforate and stimulate as needed for production.

MUD PROGRAM: FW Gel/LCM to 1150'; FW to 5200'; Cut brine/KCL to 7200'; Cut brine/KCL/Starch to TD.

BOP PROGRAM: BOP's and hydril will be installed on the 9 5/8" casing and tested daily.

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.
Signature: Ken Beardemphl

Printed name: Ken Beardemphl

Title: Landman

Date: 1-30-95

Phone: 748-1471

OIL CONSERVATION DIVISION

Approved by: SUPERVISOR, DISTRICT II

Title:

Approval Date: JAN 31 1995

Expiration Date: 7-31-95

Conditions of Approval:

Attached ☐