Submit 3 Copies to Appropriate District Office

State of New Mexico Ener_ Minerals and Natural Resources Department

Form C-103

OIL CONSERVATION DIVISION

Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240	P.O. Box 2088		30-015-28372
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexic	so 87504-2088	5. Indicate Type of Lease STATE FEE X
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	l		6. State Oil & Gas Lease No.
(DO NOT USE THIS FORM FOR P DIFFERENT RES (FORM	OTICES AND REPORTS ON WITH PROPOSALS TO DRILL OR TO DEEP SERVOIR. USE "APPLICATION FOR I C-101) FOR SUCH PROPOSALS.)	FU OH LING BYCK IO Y	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL WELL X WELL	OTHER		Tackitt AOT
2. Name of Operator YATES PETROLEUM CORPO	ORATION		8. Well No.
3. Address of Operator 105 South 4th St., A			9. Pool name or Wildcat Dagger Draw Upper Penn, North
4. Well Location	660 Feet From The South	Line and1980	Feet From The East Line
Section 28	Township 19S 10. Elevation (Show when	ther DF, RKB, RT, GR, etc.)	NMPM Eddy County
11. Chec	ck Appropriate Box to Indica	te Nature of Notice, R	leport, or Other Data SSEQUENT REPORT OF:
NOTICE OF I			ALTERING CASING
ERFORM REMEDIAL WORK			
TEMPORARILY ABANDON	CHANGE PLANS	CASING TEST AND C	
PULL OR ALTER CASING	J	OTUED: Spud. r	esume drilling, surface casingX
OTHER:		& cemen	t wine estimated date of starting any proposed
 Describe Proposed or Completed C work) SEE RULE 1103. 	rperations (Clearly state all pertinent detail	us, and give periotent dutes, sich	uding estimated date of starting any proposed
pipe. Cemented to drilling a 14-3/4" 36# J-55 (1170.08' 1167'. Insert flo gilsonite, 1/4#/sa Pacesetter Lite C 1.99, weight 12.5) 14.8). PD 4:19 PM	hole with rotary tool) of casing set at 116 pat set at 1125'. Ceme ack celloseal and 2% Ca (65-35-6), 10#/sack gi 7. Tailed in with 200 7. 4-20-95. Bumped plug 111ed out at 9:00 PM 4- 1000# for 15 minutes.	Is at 6:00 PM 4-18 to 7'. 1-Texas Patt ented with 2	95. Set 80' of 20" conductor a of spud time. Resumed 3-95. Ran 26 joints of 9-5/8" tern notched guide shoe set at this and 10#/sack welger 4 6 and 800 sacks ck celloseal and 3% CaCl2 (yield the 2% CaCl2 (yield 1.32, weight cement corculated 185 sacks ours and 40 minutes. Nippled out for apple. Reduced hole
I hereby certify that the information above	s is true and complete to the best of my knowled	lge and belief. Production	Clark 4-26-95
SKINATURE & USTUS	Ylla	mre Froduction	TELEPHONE NO. 505/748-147
TYPE OR PRINT NAME RUSTY K	lein		IELEPTRATE NO. 30377.13 21.
(This space for State Use) OFF	GRVAL MONTE DE TRUBE SE C TRICE E SUI DE EBRE		APR 1 1995
		mle	