

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28374
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Hooper AMP Com
8. Well No. 4
9. Pool name or Wildcat Dagger Draw Upper Penn North
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3525' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line

Section 20

Township 19S

Range 25E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3525' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Resume drilling, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole with rotary tools at 7:15 AM 4-24-95. Reached TD of 14-3/4" hole at 9:45 AM 4-25-95.

TD 1165'. Ran 26 joints of 9-5/8" 36# J-55 (1168.11') of casing set at 1165'. 1-Texas Pattern notched guide shoe set at 1165'. Insert float set at 1115'. Cemented with 200 sacks "H", 12% thixas, 10#/sack gilsonite, 1/4#/sack celloseal and 2% CaCl2 (yield 1.55, weight 12.6) and 800 sacks Pacesetter Lite C (65-35-6), 10#/sack celloseal and 3% CaCl2 (yield 1.99, weight 12.5). Bumped plug to 1100 psi, OK. Circulated 190 sacks to pit. WOC. Drilled out at 1:00 PM 4-26-95. WOC 20 hours. Reduced hole to 8-3/4". Resumed drilling.

OIL CON. DIV.
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE Production Clerk

DATE 5-3-95

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUN
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

MAY 8 1995

CONDITIONS OF APPROVAL, IF ANY: