

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28375

Operator <u>Nearburg Prod. Co.</u>		Lease <u>Ross Ranch 22</u>		Well # <u>3</u>	
Location of Well	Unit <u>C</u>	Section <u>22</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Peterson</u>			Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
14 3/4	* 9 5/8	36 #		1300'	775 Circ
8 3/4	7	23# & 26 #		8100'	950 Circ

Casing Data:

Surface _____ joints of 9 5/8" inch 36 # Grade 15.55

(Approved) (Rejected)

Inspected by A.S. date 2-25-56

Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required _____Type of Shoe used yes Float collar used yes Btm 3 jts welded yesTD of hole 1112' Set 1112' Feet of 9 5/8" Inch 36 # Grade 15.55New-used csg. @ 1112' with 150 2200 sacks neat cement around shoe+ 800 sack 35/65 per gal. additives 6% oil, 1/4" flomalPlug down @ 9:00 (AM) (PM) (PM) Date 2-26-56Cement circulated yes No. of Sacks 2000Cemented by B.J. Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

14 3/4" hole R.T. - 43405