State of New Mexico Form C-103 Submit 3 Copies linerals and Natural Resources Department Revised 1-1-89 Energ to Appropriate District Office OIL CONSERVATION DIVISION DISTRICT I WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-28397 Santa Fe, New Mexico 87504-2088 DISTRICT II 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEE X STATEL DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: METT X Cutter APC OTHER 8. Well No. 2. Name of Operator YATES PETROLEUM CORPORATION 9. Pool name or Wildcat 3. Address of Operator Dagger Draw Upper Penn, North 105 South 4th St., Artesia, NM 4. Well Location 660 Feet From The South 660 East Line Line and Feet From The Unit Letter Range 25E **NMPM** Eddy County Township Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3475' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: **ALTERING CASING** PLUG AND ABANDON REMEDIAL WORK PERFORM REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. **CHANGE PLANS TEMPORARILY ABANDON** CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** OTHER: Resume drilling, surface casing & OTHER: cement 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Resumed drilling a 14-3/4" hole with rotary tools at 6:30 PM 5-4-95. Reached TD of 1160' at 1:15 AM 5-7-95. Ran 26 joints of 9-5/8" 36# 8rd J-55 ST&C (1165.06') of casing set at 1160'. 1-Texas Pattern notched guide shoe set at 1160'. Insert float set at 1117'. Cemented with 800 sacks Pacesetter Lite C,1/4#/sack celloseal, 5#/sack gilsonite and 3% CaCl2 (yield 2.01, weight 12.5). Tailed in with 200 sacks "C" 2% CaCl2 (yield 1.34, weight 14.8). PD 9:15 AM 5-7-95. Bumped plug to 1100 psi, OK. Circulated 200 sacks. WOC. NOTE: Cementing witnessed by Gary Robinson w OCD - Artesia. Drivled out at 9:00 AM 5-8-95. WOC 23 hours and 45 minutes. Nippled up and tested to 3090 for 10 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE RUSTLY RUSTL

TITLE -

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

MAY 1 7 1995

APPROVED BY -