

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28410

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Patriot AIZ

8. Well No. 11-H

9. Pool name or Wildcat
Dagger Draw Upper Penn, North

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter F : 1880 Feet From The North Line and 1880 Feet From The West Line
Section 21 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3489' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, conductor, resume drilling, ☒
surface casing & cement

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 1:30 PM 1-21-2000. Drilled to 80'. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified Betty w/OCD-Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 10:00 PM 1-26-2000.

TD 1162'. Reached TD at 12:15 PM 1-28-2000. Ran 26 joints of 9-5/8" 36# J-55 8rd ST&C (1167.44') of casing set at 1162'. 1-Texas Pattern notched guide shoe set at 1162'. Insert float set at 1117'. Cemented with 200 sacks "H", 10% A-10B, 1/4#/sack celloflake, 10#/sack gilsonite and 1% CaCl₂ (yield 1.52, weight 14.6) and 900 sacks 65-35-6, 1/4#/sack celloflake, 5#/sack gilsonite and 2% CaCl₂ (yield 1.98, weight 12.5). Tailed in with 200 sacks "C" and 2% CaCl₂ (yield 1.34, weight 14.8). PD 11:15 PM 1-28-2000. Bumped plug to 810 psi, OK. Circulated 15 sacks. WOC. Nipped up and tested to 3000 psi for 10 minutes, OK. Drilled out at 10:45 PM 1-29-2000. WOC 22 hours and 30 minutes. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 3, 2000
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

Jim W. [Signature]
ALG SUPERVISOR, DISTRICT II

DATE

4-7-00