Submit 3 Copies to Appropriate District Office	State of New Mexico Energ Ainerals and Natural Resources Department		Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION P.O. Box 2088		WELL API NO. 30-015-28413
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088			5. Indicate Type of Lease STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Gas Lease No. L-1897
SUNDRY NOTICES AND REPORTS ON WELLS			
( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well: OIL OL WELL X WELL	OTHER		Aparejo APA State Com
2. Name of Operator YATES PETROLEUM CORPOR	RATION	Const.	8. Well No. 3
3. Address of Operator			9. Pool name or Wildcat
105 South 4th St., Artesia, NM 88210 D			Dagger Draw Upper Penn, North
4. Well Location Unit Letter <u>B</u> : 660 Feet From The North Line and 1980 Feet From The East Line County			
Section 16	Township 195 Ray	nge 25E	NMPM Eddy County
\$77777777777777777777777777777777777777	10. Elevation (Show whether ) 3475' (		
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
NOTICE OF IN			( <sup></sup>
		REMEDIAL WORK	
	CHANGE PLANS	COMMENCE DRILLIN	
PULL OR ALTER CASING		CASING TEST AND C	
OTHER: OTHER: Spud, re and ceme			esume drilling, surface casing X
12. Describe Proposed or Completed Ope work) SEE RULE 1103.		nd give pertinent dates, incl	luding estimated date of starting any proposed
pipe. Cemented to Resumed drilling a 143/4" hole at 2:00 of casing set at 11 set at 1115'. Ceme gilsonite and 2% Ca sack celloseal, 10# 200 sacks "C" 2% Ca 1000 psi, 0K. Ceme at 120'. Received	surface. NOTE: Notifie 14-3/4" hole with rotar 0 AM 4-8-95. Ran 26 jo 59'. 1-Texas Pattern n nted with 250 sacks "H" C12 (yield 1.55, weight /sack gilsonite and 3% C12 (yield 1.33, weight ent did not circulate. permission to ready-mix	ed Ray Smith W/ y tools at 1:00 ints of 9-5/8" otched guide sl , 12% thixad, 14.6) and 800 CaCl2 (yield 1 14.8). PD 7:0 Ran Temperatur to surface.	1-95. See 80, sin 20" conductor /OCD AM 4-0-95. Reached TD of 36# 8rd J-55 ST&C (1164.70') hoe set at (1159'. Present float 1/4#/sack celloseal, 10#/sack sacks are set ter Lite (1/1/4#/ .98, weight 12 / Tailed in with 00 PM 4-8-95. Bumped plug to e Survey and found top of cement Ready-Mixed with 26 yards. /OCD - Artesia. Drilled out at bala to 8-3/4". Resumed
8:15 PM 4-10-95. W	10C 25 hours and 15 minu	d belief.	
SKONATURE Kusty	flen T	meProduction	Clerk DATE 4-12-95
TYPE OR FRINT NAME RUSTY KIE	in		<u>теlephone no. 505/748-147</u>
	- Conneg by the M. SUM Optimized By the M. SUM		APR 1 4 1995
ONDITIONS OF APPROVAL, IF ANY:	Т	1 1	