

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28414

Operator <u>Gates Petr. Corp</u>		Lease <u>Vann APD</u>		Well # <u>1</u>	
Location of Well	Unit <u>D</u>	Section <u>21</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>N.A.</u>		Type of Equipment <u>Rotary</u>			

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
14 3/4	* 9 5/8	36# J-55		1150'	1100 Circ
8 3/4	7	23# 26#		TD	1350 Circ
		J-55, N-80			

Casing Data:

Surface _____ joints of 9 5/8" inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date 5-31-95

Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required _____Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 1150' Set 1150' Feet of 9 5/8" Inch 36 # Grade J-55(New)-used csg. @ 1150' with 200 270 cc sacks neat cement around shoe+ 900 sax Pacesetter 4.75 cc additives 10# oil, 1/4" celoseal, 250 ccPlug down @ 1:30 (AM) (PM) Date 6-1-95Cement circulated yes No. of Sacks 187 ccCemented by Western Co. / O.S. Hughes Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

14 3/4" hole R.T. - 47 hours

L.D.B. - 1039'