

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

**DISTRICT I**  
P.O. Box 1980, Hobbs, NM 88240

**DISTRICT II**  
P.O. Drawer DD, Artesia, NM 88210

**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-015-28414

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Vann APD

8. Well No.

1

9. Pool name or Wildcat

Dagger Draw Upper Penn, North

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER ☐

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter D : 660 Feet From The North Line and 660 Feet From The West Line

Section 21

Township 19S

Range 25E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3498' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud, resume drilling, surface casing and cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole with rat hole machine at 5:00 PM 5-26-95. Drilled 12-1/4" hole to 75'. Reamed 12-1/4" hole to 26" hole from surface to 60'. Set 60' of 20" conductor pipe. Cemented to surface. Resumed drilling a 14-3/4" hole with rotary tools at 7:00 PM 5-29-95.

RECEIVED

TD 1150'. Reached TD at 7:00 PM 5-31-95. Ran 26 joints of 9-5/8" 36# J-55 ST&C (1170.20') of casing set at 1150'. 1-Texas Pattern notched guide shoe set at 1150'. Cemented with 200 sacks Class "H", 12% thixad, 10#/sack gilsonite, 1/2#/sack celloseal and 2% CaCl2 (yield 1.55, weight 14.6) and 900 sacks Class C 2% CaCl2 (yield 2.01, weight 12.5). Tailed in with 200 sacks Class C 2% CaCl2 (yield 2.01, weight 12.5). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.33, weight 14.8). PD 1:30 AM 6-1-95. Bumped plug to 1000 psi, OK. Circulated 183 sacks. WOC. Drilled out at 8:00 PM 6-1-95. WOC 18 hours and 30 minutes. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Rusty Klein*

TITLE

Production Clerk

DATE 6-6-95

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

**ORIGINAL SIGNED BY TIM W. GUM**  
**DISTRICT II SUPERVISOR**

APPROVED BY

TITLE

DATE

**JUN 7 1995**

CONDITIONS OF APPROVAL, IF ANY: