	Sidie of New Mexico	Form SIR
ubrit 3 Copies Appropriate sistrict Office	Energy, Minerals and Natural Resources Department	Revised 1.1-89
<u>ISTRICT I</u> O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION P.O. Box 2088	WELL API NO. 30-015-28415
<u>ISTRICT II</u> O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico 87504-2088	5. Indicate Type of Lease STATE FEE X
USTRICT III 000 Rio Brazos Rd., Aztec, NM 87410		6. State Oil & Gas Lease No.
(DO NOT USE THIS FORM FOR PRO	CES AND REPORTS ON WELLS posals to drill or to deepen or plug back to a avoir. Use "application for permit" -101) For such proposals.)	7. Lease Name or Unit Agreement Name
Type of Well: OIL OAS WELL X WELL	CTHER T	Hinkle ALD
Name of Operator YATES PETROLEUM CORPOR	ATION RECEIVED	8. Well No. 3
Address of Operator	Viz COD ANTESIA S	9. Pool name or Wildcat Dagger Draw Upper Penn, North
105 South 4th St., Art	CG.	East U
	80 Feet From The North 6. Line and 00	0 Feet From TheLast Line
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK CHANGE PLANS COMMENCE DRILLIN CASING TEST AND C	
OTHER:		
work) SEE RULE 1103. Spudded a 26" hole w Cemented to surface hole with rotary too	with rotary tools at 1:00 PM 12-6-97. NOTE: Notified OCD-Artesia of spun ols at 10:00 PM 12-9-97. TD at 9:00 PM 12-11-97. Ran 26 joint	Set 80° of 20° conductor pipe d. Resumed drilling a 14-3/4" s of 9-5/8" 36# J-55 8rd ST&C
(1148.32') of casin Insert float set at flake, 10#/sack gil 5#/sack gilsonite, in with 200 sacks "	g set at 1145. I fille 200 sacks "H", 1056'. Cemented with 200 sacks "H", sonite and 1% CaCl2 (yield 1.52, weig 1/4#/sack celloflake and 2% CaCl2 (yi C" and 2% CaCl2 (yield 1.34, weight 1 psi, OK. Cement did not circulate. op of cement at 319'. Ran 1". Tagged	10% A-10B, 1/4#/sack cello- ht 14.6) and 900 sacks 65-35-6, eld 1.90, weight 12.7). Tailed 4.8). PD 5:00 AM 12-12-97. WOC 4 hours. Ran Temperature 1 cement at 262'. Spotted 100
Survey and found to sacks "C" and 4% Ca 108', Spotted 125	sacks "C" and 4% CaCl2. PD 2:15 PM 1	12-12-97. Had fluid level 3
Survey and found to sacks "C" and 4% Ca 108'. Spotted 125 I hereby certify that the information above it	sacks "C" and 4% CaCl2. PD 2:15 PM 1	12-12-97. Had fluid level 3 CONTINUED ON NEXT PAGE:
Survey and found to sacks "C" and 4% Ca 108', Spotted 125	sacks "C" and 4% CaCl2. PD 2:15 PM 1 style and complete to the best of my knowledge and belief.	12-12-97. Had fluid level 3. CONTINUED ON NEXT PAGE:

YATES PETROLEUM CORPORATION Hinkle ALD #3 Section 28-T19S-R25E Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

from surface on 2nd stage. Tagged cement with gauge line at 25'. Ready Mixed to surface. WOC. Nippled up and tested to 3000 psi for 30 minutes. Drilled out at 9:15 AM 12-13-97. WOC 28 hours and 15 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Notified OCD-Artesia answering service - no witness.

Rusty Klein Operations Technician December 30, 1997