

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-28418
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	LG-6459
7. Lease Name or Unit Agreement Name	
Agave AAJ State	
8. Well No.	3
9. Pool name or Wildcat	Siegest Draw Abo
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3814' GR	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:	OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator	YATES PETROLEUM CORPORATION
3. Address of Operator	105 South 4th St., Artesia, NM 88210
4. Well Location	Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line
Section 32	Township 19S Range 24E NMPM Eddy County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3814' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Spud, resume drilling, surface casing ☒  
and cement (one inch)

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 12:30 PM 5-5-95. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD - Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 12:00 PM 5-8-95.

TD 1385'. Reached TD at 10:00 AM 5-12-95. Ran 31 joints of 9-5/8" 36# 8rd J-55 ST&C (1389.83') of casing set at 1385'. 1-Texas Pattern notched guide shoe set at 1385'. Float collar set at 1345'. Cemented with 200 sacks "H", 12% thixad, 1/2#/sack celloseal, 10#/sack gilsonite and 2% CaCl2 (yield 1.55, weight 14.6) and 700 sacks "C", 1/2#/sack celloseal, 10#/sack gilsonite and 3% CaCl2 (yield 2.01, weight 12.5). Tailed in with 200 sacks "C" 2% CaCl2 (yield 1.33, weight 14.8). PD 5:15 PM 5-12-95. Bumped plug to 1100 psi. OK. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 1000'. Ran 1". Tagged cement at 1048'. Spotted 100 sacks "C" 3% CaCl2. PD 1:30 AM 5-13-95. WOC 1-1/2 hour. Ran 1". Tagged cement at 758'. Spotted 200 sacks "C" 2% CaCl2. PD 4:00 AM 5-13-95. WOC 1-1/2 hour. Ran 1". Tagged cement at 1048'. Spotted 50 sacks

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Production Clerk DATE 5-15-95  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY Rusty Klein  
DISTRICT I

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

MAY 17 1995