

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28418
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG-6459
7. Lease Name or Unit Agreement Name Agave AAJ State
8. Well No. 3
9. Pool name or Wildcat Siegest Draw Abo
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3814' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line
Section 32 Township 19S Range 24E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Production casing & cement</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4240'. Reached TD at 6:00 AM 5-20-95. Ran 103 joints of 7" 23# casing as follows: 13 joints of 7" 23# J-55 LT&C sandblasted (534.75'); 35 joints of 7" 23# J-55 LT&C (1430.40'); 9 joints of 7" 23# J-55 LT&C sandblasted (371.38') and 46 joints of 7" 23# J-55 LT&C (1911.70') (Total 4248.23') of casing set at 4239'. Float shoe set at 4239'. Float collar set at 4194'. Cemented with 400 sacks Super C, 15# Poz, 11# CSE, .3% CF-2, 5% salt and 5#/sack hiesel (yield 1.69, weight 13.0). PD 3:30 PM 5-21-95. Rumped plug to 1500 psi for 5 minutes, OK. Cement did not circulate. WOC. Released rig at 7:00 PM 5-21-95.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE May 31, 1995
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY TIM W. GUM TITLE DISTRICT II SUPERVISOR DATE JUN 7 1995
CONDITIONS OF APPROVAL, IF ANY: