Submit 3 Copies to Appropriate District Office	State Of New Iv Ener Minerals and Natural Re				epartment			Form C-1 Revised 1-1-	
DISTRICT I       JIL CONSERVATION         P.O. Box 1980, Hobbs, NM 88240       Santa Fe, New Mexico 8				88		WELL APTING 30-015 5. Indicate Ty	5-28427		clst
<u>DISTRICT II</u> 811 South 1st St, Artesia, NM 8	8210					STA		FEE	x h
DISTRICT III 1000 Rio Brazos Rd, Aztec, NM	87410								¥
SUNDRY NOTICES AND REPORTS ON WELLS									
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG						7. Lease Name or Unit Agreement Name			
BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"									
(FORM C-101) FOR SUCH PROPOSALS.)									
1. Type of Well:									
OIL WELL X GAS WELL OTHER						B & B 8. Well No.			
2. Name of Operator						#8			
Nearburg Producing Company 3. Address of Operator						9. Pool name	or Wildcat		
3300 North "A" Street, Bldg 2, Ste 120, Midland, Texas 79705						Dagger D	Draw; Upper Pe	enn, No	rth
4. Well Location	<u> </u>					00	·····		
Unit Letter	1,980	: Feet From The	Sou	th Lin	e and	990	Feet From The	East	Lin
Section	22	Township	19S	Range	25E	NMPM	Eddy		County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3,447' GR									
11. Ch	eck App	propriate Box to	Indicate N	ature of N	otice, R	eport, or Oth	ner Data		
NOTICE OF INTENTION TO:						SUBSEQU	ENT REPORT OF	:	
PERFORM REMEDIAL WORK PLUG AND ABANDON			REMEDIAL WORK ALTERING CASING						
TEMPORARILY ABANDON CHANGE PLANS				COMMENCE DRILLING OPNS.					
PULL OR ALTER CASING				CASING T	CASING TEST & CEMENT JOB				
OTHER:				OTHER: Surface casing and cement.					
10.0 ¥ . 0	-1-1-1-0-	antiana (Olaartu ata	to all norting	at dataila au	nd aivo no	dinant datas i	ocluding optimated dat	to of startin	a

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

Drilled to 1,113'. C&C hole. RU and run 28 jts 9-5/8" 36# K55 STC csg. Set casing at 1,113'. C&C hole. Cement casing using 1,100 sx cement plus additives. Circ 135 sx cement to surface. WOC for 18 hrs. Cut off casing and weld on wellhead. NU BOPE and test.

JU 95-097

		نې د (۱۹۰۰ - ۱
I hereby certify that the information above is true and complete to the best of my knowledge and SIGNATURE E. Stoff Kinkarangh KS TITLE Mgr of Drilling an	belief. Id Production DATE 07/15/9	97
TYPE OR PRINT NAME E. Scott Kimbrough	TELEPHONE 915/68	6-8235
(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR APPROVED BY	DATE JUL 3	0 1997
CONDITIONS OF APPROVAL, IF ANY:		