

CONFIDENTIAL

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-105
Revised 1-1-89

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-28481

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-4397

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐

GAS WELL ☒

DRY ☐

OTHER ☐

b. Type of Completion:

NEW
WELL ☒

WORK
OVER ☐

DEEPEN ☐

PLUG
BACK ☐

DEEP
REPAIR ☐

OTHER ☐

7. Lease Name or Unit Agreement Name

TURKEY TRACK 2 STATE COM

2. Name of Operator

BASS ENTERPRISES PRODUCTION CO.

8. Well No.

1

3. Address of Operator

P.O. BOX 2760, MIDLAND, TX 79702-2760

9. Pool name or Wildcat

EDDY UNDES GRP. 8

4. Well Location

Unit Letter H : 2180 Feet From The NORTH

Line and 660

Feet From The EAST

Section 2

Township 19S

Range 28E

NMPM

EDDY

County

10. Date Spudded

9-30-95

11. Date T.D. Reached

10-25-95

12. Date Compl. (Ready to Prod.)

12-13-95

13. Elevations (DF & RKB, RT, GR, etc.)

3424.3' GL 3441.1' KB

14. Elev. Casinghead

15. Total Depth

11,230'

16. Plug Back T.D.

11,166'

17. If Multiple Compl. How

Many Zones?

SINGLE

18. Intervals

Drilled By

Rotary Tools

0' - 11,230'

Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name

10,950'-10,984' (69 HOLES) MORROW

21. Type Electric and Other Logs Run

DLL-MSFL-GR, CNL-LDT-GR

22. Was Well Cored

NO

JAN 11 1996

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENT	RECORD	AND	PULLED
11 3/4"	42#	297'	14 3/4"	735 SX CLASS "C" SURE	1	NONE	
8 5/8"	32#	3230'	11"	1225 SX 35/65 POZ	2	NONE	
5 1/2"	17#	11,230'	7 7/8"	930 SX CLASS "H" TOC 2800		NONE	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	25. TUBING RECORD	SIZE	DEPTH SET	PACKER SET
						2 7/8"	10,828	10,828

26. Perforation record (interval, size, and number)

PERF W/3 3/8" CONVEYED GUN LOADED W/2 JSPF
AT 90° PHASED 10,950'-10,984' TOTAL 69 HOLES

27. ACID, SHOT, FRACTURE CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL

AMOUNT AND KIND MATERIAL USED

10,950'-10,984'

NONE

28. PRODUCTION

Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in)	
12-13-95		FLOWING				PRODUCING	
Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl	Gas - Oil Ratio
12-30-95	24	23/64		45	5457	2	121.267
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl	Gas - MCF	Water - Bbl	Oil Gravity - API - (Corr.)	
3050	PACKER		45	5457	2	54.9	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

SALES & LEASE USE GAS

Test Witnessed By

30. List Attachments

(1) ONE EACH ABOVE LOG

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature

R.C. Houtchens

Printed

Name

R.C. HOUTCHENS

Title SR. PROD. CLERK Date 1-9-96

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
 T. Salt 375'
 B. Salt 608'
 T. Yates 788'
 T. 7 Rivers 1000'
 T. Queen 1689'
 T. Grayburg 2055'
 T. San Andres 2539'
 T. Glorieta _____
 T. Paddock _____
 T. Blinebry _____
 T. Tubb _____
 T. Drinkard _____
 T. Abo _____
 T. Wolfcamp 8650'
 T. Penn _____
 T. Cisco (Boulevard) 9510'

T. Canyon 9726'
 T. Strawn 9946'
 T. Atoka 10243'
 T. Miss _____
 T. Devonian _____
 T. Silurian _____
 T. Montoya _____
 T. Simpson _____
 T. McKee _____
 T. Ellenburger _____
 T. Gr. Wash _____
 T. Delaware Sand _____
 T. Bone Springs 3314'
 T. MORROW 10615'
 T. LOWER MORROW 10902'
 T. RUSTLER 235'

Northwestern New Mexico

T. Ojo Alamo _____
 T. Kirtland-Fruitland _____
 T. Pictured Cliffs _____
 T. Cliff House _____
 T. Menefee _____
 T. Point Lookout _____
 T. Mancos _____
 T. Gallup _____
 Base Greenhorn _____
 T. Dakota _____
 T. Morrison _____
 T. Todilto _____
 T. Entrada _____
 T. Wingate _____
 T. Chinle _____
 T. Permian _____
 T. Penn "A" _____

T. Penn. "B" _____
 T. Penn. "C" _____
 T. Penn. "D" _____
 T. Leadville _____
 T. Madison _____
 T. Elbert _____
 T. McCracken _____
 T. Ignacio Otzte _____
 T. Granite _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____
 T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from 10950 to 10984
 No. 2, from 9440 to 9465
 No. 3, from _____ to _____
 No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
210	275	65	REDBED, SS & SHALE	8250	8690	440	SAND, SILT, DOLOMITE, SHALE
275	375	100	ANHYDRITE, SALT	8690	10355	1665	LIMESTONE, SHALE
375	608	233	SALT	10355	10440	85	SAND, SHALE, LIMESTONE
608	788	180	ANHYDRITE, SHALE	10440	10540	100	LIMESTONE, SHALE
788	815	27	SS, SHALE	10540	10580	40	SAND, LIMESTONE, SHALE
815	1690	875	ANHYDRITE, DOLOMITE, SHALE	10580	10774	194	LIMESTONE, SHALE, CHERT
1690	1725	35	SAND	10774	11080	306	SAND, SHALE, LIMESTONE
1725	2190	465	DOLO, ANHY, SAND, SHALE	11080	11230	150	SHALE, LIMESTONE
2190	2215	25	SAND				
2215	3315	1100	DOLOMITE				
3315	4570	1255	LIMESTONE				
4570	4608	38	DOLOMITE				
4608	6516	1908	LIMESTONE				
6516	6630	114	SAND, SHALE, LIMESTONE				
6630	7380	750	LIMESTONE, SHALE				
7380	7660	280	SAND, SHALE, LIMESTONE				
7660	8040	380	LIMESTONE, SHALE, DOLOMITE				
8040	8070	30	SAND, SILT, LIMESTONE, SHALE				
8070	8250	180	LIMESTONE, SHALE				