

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-28519
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	SAVANNAH STATE (17133)
8. Well No.	1
9. Pool name or Wildcat	BOYD; MORROW (72480)

Section	32	Township	19 S	Range	25 E	NMMPM	EDDY	County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)								
3502								

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. Name of Operator CONOCO INC <005073>
3. Address of Operator 10 Desta Drive Ste 100 W. Midland, TX 79705	4. Well Location Unit Letter A : 660 Feet From The NORTH Line and 660 Feet From The EAST Line Section 32 Township 19 S Range 25 E NMMPM EDDY County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3502	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐	OTHER: SPUD SET SURFACE CSG ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-23-95 MIRU. SPUD 14 3/4" HOLE @ 8 am. DRILL TO A DEPTH OF 1177'.
GIH W/ 25 JTS 9 5/8" 36# K-55 ST&C CSG SET @ 1177'.
SHOE SET @ 1177'. COLLAR SET @ 1131'. LEAD SLURRY 200 SX CLASS 'H' W/ 12% GYPSUM + 1%
CACL2 + 10#/SX GILSONITE & 1/4#/SX CELLO. MIDDLE SLURRY 950 SX PA
W/ 5#/SX GILSONITE + 2% CACL2 + 1/4#/SX CELLO FLAKE. TAIL SLURRY 120 SX CLASS
W/ 2% CACL2. DISPLACED W/ 87.31bbl FRESH WATER. CEMENT RETURNS OF 80 SX. BUMPED PLUG @
3:30 pm OF 7-25-95 W/ 500 PSI. NMOC WAS ON LOCATION DURING THE CEMENT JOB ON 7-25-95.
CONTINUE DRILLING 8 3/4" HOLE TO TD.

AUG 08 1995

OIL CON. DIV.
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bill R. Keathly TITLE SR. REGULATORY SPEC. DATE 8-7-95
TYPE OR PRINT NAME BILL R. KEATHLY TELEPHONE NO. 915-686-5424

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE AUG 10 1995
CONDITIONS OF APPROVAL, IF ANY: