

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO. 30-015-28542

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
LG-864

7. Lease Name or Unit Agreement Name
Amole AMM State Com

8. Well No.
4

9. Pool name or Wildcat
Dagger Draw Upper Penn, North

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

b. Type of Completion:
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1471

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter I : 1980 Feet From The South Line and 660 Feet From The East Line
Section 16 Township 19S Range NMPM Eddy County

10. Date Spudded
RH 3-4-98
RT 3-8-98

11. Date T.D. Reached
3-25-98

12. Date Compl. (Ready to Prod.)
4-16-98

13. Elevations (DF& RKB, RT, GR, etc.)
3476' GR

14. Elev. Casinghead

15. Total Depth
8230'

16. Plug Back T.D.
8161'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By
Rotary Tools
80-8230'

19. Producing Interval(s), of this completion - Top, Bottom, Name
7684-7727' Canyon

20. Was Directional Survey Made
No

21. Type Electric and Other Logs Run
CNL, BHC & Laterolog

22. Was Well Cored
No

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
20"		80'	26"	Cement to surface	
9-5/8"	36#	1185'	14-3/4"	1470 sx - circulate	
7"	26# & 23#	8230'	8-3/4"	900 sx - circulate	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-7/8"	7812'	

26. Perforation record (interval, size, and number)
7684-7727' w/25 .42" holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
7684-7727'	Acidized w/1500 gals 20% iron control HCL acid & BS. Re-acidized w/15000 gals 20% gelled iron control HCL acid & BS

PRODUCTION

28. Date First Production
4-17-98

Production Method (Flowing, gas lift, pumping - Size and type pump)
Pumping

Well Status (Prod. or Shut-in)
Producing

Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
4-28-98	24			112	410	885	3661:1
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
			112	410	885	42.6	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
Sold - connected to Dagger Draw Gas Processing

Test Witnessed By
Juan Fuentes

30. List Attachments

Deviation survey & logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Rusty Klein Printed Name Rusty Klein Title Operations Tech. Date 4-29-98

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____	T. Canyon _____ 7650'
T. Salt _____	T. Strawn _____
B. Salt _____	T. Atoka _____
T. Yates _____	T. Miss _____
T. 7 Rivers _____	T. Devonian _____
T. Queen _____	T. Silurian _____
T. Grayburg _____	T. Montoya _____
T. San Andres _____ 762'	T. Simpson _____
T. Glorieta _____ 2302'	T. McKee _____
T. Paddock _____	T. Ellenburger _____
T. Blinberry _____	T. Gr. Wash _____
T. Tubb _____	T. Delaware Sand _____
T. Drinkard _____	T. Bone Springs _____ 3704'
T. Abo _____	T. _____
T. Wolfcamp _____ 5912'	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todillo _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 3, from.....to.....
No. 2, from.....to.....	No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1185	1185	Surface & redbed				
1185	3822	2637	Dolomite				
3822	4056	234	Dolomite & lime				
4056	4276	220	Dolomite				
4276	5058	782	Lime				
5058	5243	185	Lime & shale				
5243	5379	136	Lime, sand & dolomite				
5379	5488	109	Lime				
5488	6145	657	Dolomite, shale & sand				
6145	6341	196	Shale & lime				
6341	6878	537	Dolomite				
6878	7080	202	Shale				
7080	7273	193	Shale & sand				
7273	7445	172	Shale				
7445	8024	579	Lime & shale				
8024	8230	206	Dolomite & lime				