

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28543

Operator <u>Yates Petr Corp</u>		Lease <u>Marshall APH</u>		Well # <u>1</u>	
Location of Well	Unit <u>F</u>	Section <u>9</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>NA</u>	Type of Equipment <u>R</u>				

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
14 3/4	* 9 5/8	36# J-55		1150	1100 Circ
8 3/4	7	23# J-55		8300' TD	1350 Circ
		26# N-80			

Casing Data:

Surface _____ joints of 9 5/8" inch 26 # Grade J-55

(Approved) (Rejected)

Inspected by A.S. date 8.3.95

Cementing Program

Size of hole 14 3/4" Size of Casing 9 5/8" Sacks cement required _____Type of Shoe used guide Float collar used insect Btm 3 jts welded yesTD of hole 1115' Set 1115' Feet of 9 5/8" Inch 26 # Grade J-55(New)-used csg. @ 1115' with 200 290cc sacks neat cement around shoe+ 900 sax P/L-C additives 10# gilsonite, 1/2# celoseal, 290ccPlug down @ 3:30 (AM) (PM) Date Aug. 4-95Cement circulated yes No. of Sacks 1850xCemented by B.J. Hughes Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

L.D.B. - 995'

14 3/4" hole B.T. 26 hours.