Submit 3 Copies to Appropriate District Office	State of New Me Energ, inerals and Natural Re		Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobba, NM 88240 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III	OIL CONSERVATIO P.O. Box 208 Santa Fe, New Mexico	8	WELL API NO. <u>30-015-28557</u> 5. Indicate Type of Lesse STATE X FEE
1000 Rio Brazos Rd., Aztec, NM 87410	CES AND REPORTS ON WEL	S	6. State Oil & Gas Lease No. E-10167
( DO NOT USE THIS FORM FOR PRO DIFFERENT RESER (FORM C-	VOR. USE "APPLICATION FOR PER- 101) FOR SUCH PROPOSALE	OB PLUG BACK TO.A.	7. Lease Name or Unit Agreement Name
1. Type of Well: OL WELL X WELL OAS WELL	OTHER	AN 1 4 1097	Boyd X State Com
<ol> <li>Name of Operator YATES PETROLEUM CORPORA</li> <li>Address of Operator 105 South 4th St., Arte</li> </ol>			8. Well No. 11 <sup>o</sup> 9. Pool mame or Wildcat Dagger Draw Upper Penn, North
4. Well Location Unit Letter : :	) Feet From The South	Line and73	0 Feet From The East Line
Section 16	Township 19S Ram 10. Elevation (Show whether 3485	OF, RKB, RT, GR, etc.)	NMPM Eddy County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
		REMEDIAL WORK	
		COMMENCE DRILLING	
PULL OR ALTER CASING CASING TEST AND CEMENT JOB			
DTHER:		OTHER: Resume dr	rilling, surface casing & cmt [X]
work) SEE RULE 1103.			ling estimated date of starting any proposed
Resumed drilling a $14-3/4$ " hole with rotary tools at 4:00 PM $1-4-97$ .			
casing set at 1165'. at 1120'. Cemented w: flocele and 1% CaCl2 gilsonite, 1/4#/sack sacks Class C 2% CaCl psi, OK. Cement did of cement at 175'. R PD 9:30 PM 1-8-97. C minutes, OK. Cut off	1-Texas Pattern notche ith 100 sacks Class "C (yield 1.36, weight 14 flocele and 3% CaC12 ( 2 (yield 1.34, weight not circulate. WOC 4 1 an 1". Tagged cement irculated 25 sacks. We	ed guide shoe se ' (veraset), 5#, .8) and 900 sach yield 2.01, weig 14.8). PD 1:00 nours. Ran Temp at 175'. Spotte DC. Nippled up pple. Drilled of	9-5/8" 36# J-55 (1170.42') of et at 1165'. Insert float set /sack gilsonite, 1/4#/sack ks Halliburton Lite "C", 5#/sack ght 12.5). Tailed in with 200 PM 1-8-97. Bumped plug to 525 perature Survey and found top ed 450 sacks Class C cement. and tested to 1000 psi for 30 out at 12:30 AM 1-10-97. WOC drilling.
I hereby certify that the information above is true		belief. Operations'Te	echnician Jan. 13, 1997
SKONATURE USLUT A		LE :::::::::::::::::::::::::::::::	TELEPHONE NO. 505/748-147
(This space for State Use)	176 87 1941 X 2 14	<u></u>	JAN 21 1997
	The second se	LE	DATE

\_