

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2068
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-28631

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Patrick API

8. Well No.

2

9. Pool name or Wildcat

Dagger Draw Upper Penn, North

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER ☐

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line

Section 9 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3519' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud, resume drilling, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 1:00 PM 11-30-95. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 2:30 PM 12-4-95.

TD 1162'. Reached TD at 6:45 PM 12-5-95. Ran 26 joints of 9-5/8" 36# J-55 ST&C (1167.89') of casing set at 1162'. 1-Texas Pattern notched guide shoe set at 1162'. Insert float set at 1117'. Cemented with 200 sacks Thickset, 1/4#/sack flocele, 5#/sack gilsonite and 2% CaCl2 (yield 1.42, weight 14.6) and 800 sacks Howco Lite C, 1/4#/sack flocele, 10#/sack gilsonite and 3% CaCl2 (yield 2.01, weight 12.4). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 2:45 AM 12-6-95. Bumped plug to 800 psi, OK. Circulated 200 sacks. WOC. Nipped up and tested to 3000 psi for 10 minutes, OK. Drilled out at 11:00 PM 12-6-95. WOC 18 hours and 15 minutes. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Production Clerk

DATE

12-8-95

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM

APPROVED BY

TITLE

DATE

DEC 18 1995

CONDITIONS OF APPROVAL, IF ANY: