	OLL CONSERV 3.1st ST.		L CONSERVATION DIV	
		L. A.	3. 1st ST. HTESIA, NM 88210-2834 CS	
orm 3160-5 une 1990)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.	
		NM-62211		
Do not use this	form for proposals to drill	ND REPORTS ON WELLS for to deepen or reentry to a different rese PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name rvoir.	
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation	
			8. Well Name and No.	
2. Name of Operator	ROLEUM CORPORATION	(505) 748–1471)	Hanagan APL Fed Com #1. 9. API Well No.	
3. Address and Telephone No.			<u>30-015-38635</u> 10. Field and Pool, or Exploratory Area	
105 South 4th St., Artesia, NM 88210 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			Hackberry Morrow	
		on 31-T19S-R3OE (Unit G, SWNE)	11. County or Parish, State	
			Eddy Co., NM	
2. CHEC	K APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, I	REPORT, OR OTHER DATA	
ТҮРЕ (OF SUBMISSION	TYPE OF A	CTION 2	
	ice of Intent	Abandonment Recompletion	Change of Plans	
X Sub	sequent Report	Plugging Back	Non-Routine Fracturing	
🗍 Fina	al Abandonment Notice	Altering Casing X Other Perforate & acid	Lize Dispose Water (Note: Report results of multiple completion on Well	
			Completion or Recompletion Report and Log form)	
13. Describe Proposed o	or Completed Operations (Clearly state all po	ertinent details, and give pertinent dates, including estimated date	of starting any proposed work. If well is directionally drilled,	
give subsurface 11-14-95 down. Loa up BOP. T 10836' w/2 14, 16, 18 down wirel 11-15-95 3000 psi, Tested ann Acidized p Shut down. installed 11-16-95 installed 11-17-95 11-18-95	 clocations and measured and true vertical Rigged up slick line aded tubing with 2% Kernel COOH with tubing and ernel COOH and arnel COOH arnel	dephs for all markers and zones pertinent to this work.)" e and set standing valve in pac CL water. Got off on/off tool. on/off tool. TIH with 4" casin - 1 SPF) as follows: 10798, 1 , 30, 32 34 & 10836'. TOOH wit packer and 2-7/8" tubing. Shut BP, packer and tubing. Set RBP t packer at 10718'. Nippled do . Swabbed tubing fluid level d 836' with 3000 gallons 15% NEFE ubing down. Reversed tubing cl t 10718'. TOOH. TIH with pack '. Tested annulus to 1000 psi, g.	ker at 11012'. Bled tubing Nippled down tree and nippled g guns and perforated 10798- 0800, 02, 04, 06, 08, 10, 12, h 4" casing guns and rigged down. at 10972'. Tested RBP to wn BOP. Installed tree. own. Rigged up tree saver. genet actic and ball sealers. eas. Nippled down tree and er and tubing. OK. Nippled down BOP and	
give subsurface 11-14-95 down. Loa up BOP. T 10836' w/2 14, 16, 18 down wirel 11-15-95 3000 psi, Tested ann Acidized p Shut down. installed 11-16-95 installed 11-17-95 11-18-95 Nippled do	 clocations and measured and true vertical Rigged up slick line aded tubing with 2% Kernold COOH with tubing and coordinate COOH and coordinat	dephs for all markers and zones perfinent to this work.)" e and set standing valve in pac CL water. Got off on/off tool. on/off tool. TIH with 4" casin - 1 SPF) as follows: 10798, 1 , 30, 32 34 & 10836'. TOOH wit packer and 2-7/8" tubing. Shut BP, packer and tubing. Set RBP t packer at 10718'. Nippled do . Swabbed tubing fluid level d 836' with 3000 gallons 15% NEFE ubing down. Reversed tubing cl t 10718'. TOOH. TIH with pack '. Tested annulus to 1000 psi, g. abbed. Shut down. 1 and latched onto packer at 11	<pre>ker at 11012'. Bled tubing Nippled down tree and nippled g guns and perforated 10798- 0800, 02, 04, 06, 08, 10, 12, h 4" casing guns and rigged down. at 10972'. Tested RBP to wn BOP. Installed tree. own. Rigged up tree saver. genet actid and train sealers. easil Nippled down tree and er and tubing. OK. Nippled down BOP and </pre>	
give subsurface 11-14-95 down. Loa up BOP. T 10836' w/2 14, 16, 18 down wirel 11-15-95 3000 psi, Tested ann Acidized p Shut down. installed 11-16-95 installed 11-17-95 11-18-95 Nippled do	 clocations and measured and true vertical Rigged up slick line aded tubing with 2% K COOH with tubing and a CO. 41" holes (Strawn 20, 22, 24, 26, 28 Line. TIH with RBP, 1 Finished TIH with RBP, 1 Finished TIH with R OK. Moved up and se nulus to 1000 psi, OK perforations 10798-100 Bled annulus and to BOP. Unset packer a Set packer at 10701 tree. Began swabbin Bled well down. Sw TIH with on/off too Down BOP and nippled u 	dephs for all markers and zones perfinent to this work.)" e and set standing valve in pac CL water. Got off on/off tool. on/off tool. TIH with 4" casin - 1 SPF) as follows: 10798, 1 , 30, 32 34 & 10836'. TOOH wit packer and 2-7/8" tubing. Shut BP, packer and tubing. Set RBP t packer at 10718'. Nippled do . Swabbed tubing fluid level d 836' with 3000 gallons 15% NEFE ubing down. Reversed tubing cl t 10718'. TOOH. TIH with pack '. Tested annulus to 1000 psi, g. abbed. Shut down. 1 and latched onto packer at 11	<pre>ker at 11012'. Bled tubing Nippled down tree and nippled g guns and perforated 10798- 0800, 02, 04, 06, 08, 10, 12, h 4" casing guns and rigged down. at 10972'. Tested RBP to wn BOP. Installed tree. own. Rigged up tree saver. genet actid and train sealers. easil Nippled down tree and er and tubing. OK. Nippled down BOP and </pre>	
give subsurface 11-14-95 down. Loa up BOP. T 10836' w/2 14, 16, 18 down wirel 11-15-95 3000 psi, Tested ann Acidized p Shut down. installed 11-16-95 installed 11-17-95 11-18-95 Nippled do 14 I hereby certify the Signed	 clocations and measured and true vertical Rigged up slick line aded tubing with 2% K COOH with tubing and a CO. 41" holes (Strawn 20, 22, 24, 26, 28 Line. TIH with RBP, 1 Finished TIH with RBP, 1 Finished TIH with R OK. Moved up and se nulus to 1000 psi, OK perforations 10798-100 Bled annulus and to BOP. Unset packer a Set packer at 10701 tree. Began swabbin Bled well down. Sw TIH with on/off too Down BOP and nippled u 	dephs for all markers and zones pertinent to this work.)* e and set standing valve in pac CL water. Got off on/off tool. on/off tool. TIH with 4" casin - 1 SPF) as follows: 10798, 1 , 30, 32 34 & 10836'. TOOH wit packer and 2-7/8" tubing. Shut BP, packer and tubing. Set RBP t packer at 10718'. Nippled do . Swabbed tubing fluid level d 836' with 3000 gallons 15% NEFE ubing down. Reversed tubing cl t 10718'. TOOH. TIH with pack '. Tested annulus to 1000 psi, g. abbed. Shut down. 1 and latched onto packer at 11 p tree. Flanged up. Shut well	<pre>ker at 11012'. Bled tubing Nippled down tree and nippled g guns and perforated 10798- 0800, 02, 04, 06, 08, 10, 12, h 4" casing guns and rigged down. at 10972'. Tested RBP to wn BOP. Installed tree. own. Rigged up tree saver. each Nippled down tree and er and tubing. OK. Nippled down BOP and OML for with packer. in. DIST. 2 Date Nov. 20, 1995</pre>	
give subsurface 11-14-95 down. Loa up BOP. T 10836' w/2 14, 16, 18 down wirel 11-15-95 3000 psi, Tested ann Acidized p Shut down. installed 11-16-95 installed 11-17-95 11-18-95 Nippled do 14 I hereby certify the Signed	c locations and measured and true vertical - Rigged up slick line aded tubing with 2% K COOH with tubing and a 20.41" holes (Strawn 3, 20, 22, 24, 26, 28 line. TIH with RBP, - Finished TIH with RBP, OK. Moved up and se nulus to 1000 psi, OK perforations 10798-10 Bled annulus and t BOP. Unset packer a - Set packer at 10701 tree. Began swabbin - Bled well down. Sw - TIH with on/off too own BOP and nippled u C Manufactories use - State office use - State office use	dephs for all markers and zones pertinent to this work.)" e and set standing valve in pac CL water. Got off on/off tool. on/off tool. TIH with 4" casin - 1 SPF) as follows: 10798, 1 , 30, 32 34 & 10836'. TOOH wit packer and 2-7/8" tubing. Shut BP, packer and tubing. Set RBP t packer at 10718'. Nippled do . Swabbed tubing fluid level d 836' with 3000 gallons 15% NEFE ubing down. Reversed tubing cl t 10718'. TOOH. TIH with pack '. Tested annulus to 1000 psi, g. abbed. Shut down. 1 and latched onto packer at 11 p tree. Flanged up. Shut well	<pre>ker at 11012'. Bled tubing Nippled down tree and nippled g guns and perforated 10798- 0800, 02, 04, 06, 08, 10, 12, h 4" casing guns and rigged down. at 10972'. Tested RBP to wn BOP. Installed tree. own. Rigged up tree saver. genet actid and balt sealers. eas.! Nippled down tree and er and tubing. OK. Nippled down BOP and </pre>	