

FIELD REPORT FOR CEMENTING OF WELLS

C. CONSERVATION DIVISION

30-015-2866

Operator <u>Yates Petr. Corp.</u>		Lease <u>Binger AKU</u>		Well # <u>2</u>	
Location of Well	Unit <u>G</u>	Section <u>29</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>NA</u>		Type of Equipment <u>R</u>		

APPROVED CASING PROGRAM

* Witness A/S

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	* <u>9 5/8</u>	<u>36# J-55</u>	<u>1</u>	<u>1150'</u>	<u>1100 Circ</u>
<u>8 3/4</u>	<u>7</u>	<u>23# 26#</u>		<u>TD</u>	<u>1350 Circ</u>
		<u>J-55, N-80</u>			

Casing Data:

Surface 22 joints of 9 5/8 inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by Mike Stubbfield date 11/17/95

Cementing Program

Size of hole 14 3/4 Size of Casing 9 5/8 Sacks cement required 1100Type of Shoe used Notch Float collar used insert Btm 3 jts welded YesTD of hole 1155 Set 1157 Feet of 9 5/8 Inch 36 # Grade J-55New-used csg. @ 900 lbs / 2000 yds with 200 sacks neat cement around shoe+ sax additives 10 lbs / 50 gals / 28 ccPlug down @ 1:30 (AM) (PM) Date 11/19/95Cement circulated Yes No. of Sacks 197 to pitCemented by Habberton Witnessed by [Signature]

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 1-3-5 conditions