

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28738
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-10167
7. Lease Name or Unit Agreement Name Boyd X State Com
8. Well No. 12
9. Pool name or Wildcat Dagger Draw Upper Penn. North

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter <u>H</u> : <u>1780</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>16</u> Township <u>19S</u> Range <u>25E</u> NMPM <u>Eddy</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3469' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine, at 3:30 PM 3-5-96. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 6:00 AM 3-8-96.

TD 1162'. Reached TD at 1:15 PM 3-9-96. Ran 26 joints of 9-5/8" 36# J-55 8rd ST&C (1165.15') of casing set at 1162'. 1-Texas Pattern notched guide shoe set at 1162'. Insert float set at 1117'. Cemented with 200 sacks Thixset, 5#/sack gilsonite, 1/4#/sack flocele and 2% CaCl2 (yield 1.55, weight 14.6) and 800 sacks Halliburton Lite Premium Plus (65-35-6), 5#/sack gilsonite, 1/4#/sack flocele and 3% CaCl2 (yield 2.01, weight 12.5). Tailed in with 200 sacks Premium Plus with 2% CaCl2 (yield 1.34, weight 14.8). PD 9:15 PM 3-9-96. Bumped plug to 800 psi, OK. Circulated 310 sacks. WOC. Nipped up and tested to 1000 psi for 30 minutes, OK. Drilled out at 3:15 PM 3-10-96. WOC 18 hours. Reduced hole to 8-3/4". Resumed drilling. NOTE: Cementing witnessed by Mike Stubblefield w/OCD-Artesia.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 3-13-96
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAR 18 1996

CONDITIONS OF APPROVAL, IF ANY: