

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28748
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Marshall APH
8. Well No. 2
9. Pool name or Wildcat Dagger Draw Upper Penn, North
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3535' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter E : 1980 Feet From The North Line and 660 Feet From The West Line Section 9 Township 19S Range 25E NMPM Eddy County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, Resume Drilling, Surface Casing, Cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine, at 2:00 PM 1-9-96. Set 80' of 20" conductor pipe. Cemented to surface. Resumed drilling a 14-3/4" hole with rotary tools at 5:15 PM 1-12-96.

TD 1160'. Reached TD at 2:30 AM 1-14-96. Ran 26 joints of 9-5/8" 36# J-55 8rd St (1163.02') of casing set at 1160'. 1-Texas Pattern notched guide shoe set at 1160'. Insert float set at 1115'. Cemented with 200 sacks "H", 10% A-11, 2% AN 22 1996 #/sack cello seal and 10#/sack gilsonite (yield 1.56, weight 14.6) and 900 sacks Poz C (65-35-6), 10#/sack gilsonite, 1/4#/sack cello seal and 2% CaCl2 (yield 1.98, weight 15.5) 10:00 AM 1-14-96. Bumped plug to 1000 psi, float did not hold. Left 400 psi on well and shut in. Circulated 195 sacks. WOC. Nipped up and tested to 1000 psi for 20 minutes. Drilled out at 4:00 AM 1-15-96. WOC 18 hours. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 1-17-96
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

JAN 26 1996

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: