

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 1980' FWL of Section 9-T19S-R25E (Unit N, SESW)

5. Lease Designation and Serial No.

NM-1372

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Warren ANW Federal #7

9. API Well No.

30-015-28839

10. Field and Pool, or Exploratory Area

Dagger Draw Upper Penn, No.

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 26" hole with rat hole machine at 10:30 AM 5-10-96. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified Cathy Queen w/BLM-Carlsbad of spud. Resumed drilling a 14-3/4" hole with rotary tools at 3:15 PM 5-12-96.

TD 1160'. Reached TD at 11:00 PM 5-13-96. Ran 26 joints of 9-5/8" 36# J-55 8rd ST&C (1165.57') of casing set at 1160'. 1-Texas Pattern notched guide shoe set at 1160'. Insert float set at 1115'. Cemented with 200 sacks "H", 10% A-11, 1% CaCl2, 1/2#/sack celloflake and 10#/sack gilsonite (yield 1.51, weight 14.63) and 700 sacks Lite (65-35-6), 10#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.98, weight 12.52). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 5:45 AM 5-14-96. Bumped plug to 1000 psi, OK. Circulated 227 sacks. WOC. Nippled up and tested to 3000 psi for 30 minutes, OK. Drilled out at 1:00 AM 5-15-96. WOC 19 hours and 15 minutes. Reduced hole to 8-3/4". Resumed drilling.

ACCEPTED FOR RECORD

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date May 15, 1996

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: