

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-28981

Operator <u>Hearburg Prod. Co.</u>		Lease <u>Osage Boyd 15</u>		Well # <u>7</u>	
Location of Well	Unit <u>L</u>	Section <u>15</u>	Township <u>19</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Peterson</u>	Type of Equipment <u>Rotary</u>				

APPROVED CASING PROGRAM

* Witness 9 5/8

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	* <u>9 5/8</u>	<u>36 #</u>		<u>1100</u>	<u>700 Circ</u>
<u>8 3/4</u>	<u>7</u>	<u>23 # + 26 #</u>		<u>8300</u>	<u>950 Circ</u>
					<u>Tie Back To Surf</u>

Casing Data:

Surface 26 joints of 9 5/8 inch 36 # Grade K-55

(Approved) (Rejected)

Inspected by Ken Livingston date 5-29-96

Cementing Program

Size of hole 14 3/4 Size of Casing 9 5/8 Sacks cement required 700 CircType of Shoe used Tex Float coliar used Insert Btm 3 jts welded HAI weldTD of hole 1126 Set 1126 Feet of 9 5/8 Inch 36 # Grade K-55New-used csg. @ 1126 with 150 SxL sacks neat cement around shoe200 sax thick set additives 10% Gyp 10% Gel 4% Cacl₂ 1/4" cellotapePlug down @ 6:15 (AM) (PM) Date 5-29-96Cement circulated yes No. of Sacks 158 st to pitCemented by B. J. Witnessed by Ken Livingston

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 800 SxL 35/65 Pos C 6% Gel 2% Cacl₂ 1/4" cellotape