

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
**30-015-29043**

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
**E-1051-7**

7. Lease Name or Unit Agreement Name

**MILLMAN "11" STATE**

8. Well No.  
**3**

9. Pool name or Wildcat  
**MILLMAN; (QU-GB-SA), EAST**

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
**MARALO, INC.**

3. Address of Operator  
**P. O. BOX 832, MIDLAND, TX 79702**

4. Well Location

Unit Letter **J** : **1980** Feet From The **SOUTH** Line and **1830** Feet From The **EAST** Line

Section **11** Township **19S** Range **28E** NMPM **EDDY** County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

**3437' GR**

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

08/11/96 SPUD @ 10:00 PM.

08/12/96 RU CAPSTAR RIG #5, DRILLED SURFACE HOLE TO 423', CIRCULATED HOLE CLEAN FOR 8-5/8" CSG, RUN 10 JTS 8-5/8" 24# K-55 ST&C CSG. SET @ 423'.

08/13/96 CEMENTED 8-5/8" CSG W/350 SXS PREM PLUS CMT W/2% CACL2. CEMENT CIRC'D TO SURFACE, 4 HRS WOC, CUT OFF 8-5/8" CSG & WELDED ON 8-5/8" BRADENHEAD, NU BOP, TESTED BOP & CHOKE TO 1000 PSI, OK. RIG REPAIR.

08/18/96 DEPTH OUT 2746'. CIRC HOLE FOR LOGS.

08/19/96 RU BWSO & RAN CNL/LDT/AIT/GR 2746' TO 423' W/GR/CNL TO SURFACE. RAN 64 JTS 15.5# CSG, SET @ 2746', CEMENTED 5-1/2" CSG W/520 SXS HALCO LIGHT CEMENT W/1/4# FLOCELE & 5# GILSONITE + 120 SXS PREM PLUS CLASS "C" CEMENT W/.6% HALAD 322 + 5# SALT. PLUG DOWN @ 5:50 PM 08/19/96. ND BOP, SET 5-1/2" CSG SLIP, CUT OFF 5-1/2" CSG. NU WELLHEAD. RELEASED RIG.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dorothea Logan TITLE REGULATORY ANALYST DATE AUGUST 20, 1996  
TYPE OR PRINT NAME DOROTHEA LOGAN TELEPHONE NO. (915) 684-7441

(This space for State Use)

**ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR**

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE AUG 26 1996

CONDITIONS OF APPROVAL, IF ANY: